JVC VN-H557U

NETWORK HD PTZ INDOOR DOME CAMERA

SuperLoLux HD™

Features:

- 1920 x 1080 Full HD stream [Motion JPEG, H.264 High Profile]
- 10x optical zoom, 10x digital zoom
- 350 deg. Non-endless Pan/Tilt performance
- SLL sensitivity 0.45 lux color
- 3DNR, Privacy mask, Motion detection
- Alarm IN / OUT function
- Audio communication
- SD card recording
- PoE / 24VAC / 12VDC power supply
- Optional bracket for flush mounting
- Multi angle installation available
- MTBF 30,000 H

Wider Area coverage by one camera

Multi angle installation: Ceiling/Desktop

Distributed by:
XORTEC
INFORMATION TECHNOLOGY
..... FOR YOUR BUSINESS!

XORTEC GmbH
Berner Strasse 79
60437 Frankfurt am Main
Germany

Phone: +49 69 5069886-0
Fax: +49 69 5069886-29
www.xortec.de

JVC

Specifications:

	VN-H557U
Camera, Lens and Pan/Tilt	
Image device	Super LoLux 1 / 2.8 inch 2 Megapixel CMOS
Minimum. Illumination	Color: 0.45 lx (AGC HIGH, x2, 50%) , 0.2 lx (AGC HIGH, x2, 25%) B&W: 0.35 lx (AGC HIGH, x2, 50%) , 0.2 lx (AGC HIGH, x2, 25%)
PTZ function	10x Optical, and 10x digital zoom, 100 preset positions Auto return / Auto flip / Auto pan Pan: +/- 175 deg, Non-endless, Speed approx. 1 deg/s to 300 deg/s Tilt: -30 to90 deg (Desktop), 90 to -30 deg (Ceiling), Speed approx. 1 deg/s to 170 deg/s Pan/Tilt command latency : 50ms
Lens	F1.8 6.3 – 63.3 mm, Auto / Manual iris control
White balance	Manual / ATW-Wide / ATW-Narrow / ATW-Full / AWC
Sens-up	Yes (x32)
Noise reduction	3DDNR
BLC	Yes (4 areas)
Day/Night	Easy Day/Night
Scene file	8 patterns
Motion detect	Yes
Privacy mask	Yes (8 areas)
Network	
Picture resolution	1920x 1080, 1280x720, 640x360, 1280x960, 640x480, 320x240, 720x480, 352x240
Max frame rate	H.264 High Profile / Baseline : 30 fps, Motion JPEG : 30 fps
Multi stream	1920x1080@30fps/H.264 HP, 720x480@30fps/H.264 HP 1920x1080@30fps/H.264 HP,720x480@30fps/MJPEG 1920x1080@30fps/H.264 HP,352x240@30fps/H.264 HP,352x240@30fps/MJPEG
Protocol	IPv4, HTTP, HTTPS, TCP, RTSP/RTCP/RTP, ICMP, UDP, IGMP, DNS, DHCP, ARP, NTP, FTP, SMTP, NTP, SNMP, AMX Device discovery, JVC API, ONVIF v2.1
Internet explorer	IE 8/9 and IE10 on Windows 8
General	
Local recording	SDHC (Continuous recording / Alarm recording / Export by MPEG-4 format)
Audio communication	Yes (In/Out) mu-low
Alarm and trigger	Input (2), Output (2), Position, Sound/Motion/Tamper detect, Time, Day/Night
Power	PoE 12W, 24VAC 660mA, 12VDC 1000mA
Temperature range	-10 to 50°C
Dimensions (WxHxD)	dia.120 x H170.5mm
Weight Approx.	1.1 kg
Supported recorder	JVC Network video recorder : VR-X1600U/VR-X3200U, SLLHD NVR Video management software : Avigilon, Exacq, Genetec, Geovision, Milestone, SeeTec and many other VMS
Optional bracket	WB-555 [Ceiling recessed mount bracket]
Regulation	CE, RoHS2, IEE 802.3(10Base-T), IEEE 802.3u(100Base-TX), IEEE802.3af(PoE) FCC Part15 Class A, UL60950, EN60950, EN55022/2006+A1/2007<Class A>, GOST-R

Ceiling recessed bracket [Optional]



SD card slot

Connectors

Specifications subject to change without notice.
Copyright 2013 JVC KENWOOD Corporation All rights reserved.
All product names stated in this document are trademarks or registered trademarks of their respective companies. Marks such as TM, ®, and © are omitted in this document.