

**Cowichan District Hospital Replacement Project  
SCHEDULE 2: ALLIANCE WORKS AND PROJECT DESCRIPTION  
PROJECT ALLIANCE AGREEMENT  
September 9, 2022**

---

**APPENDIX 2K FOOD SERVICES SPECIFICATIONS  
ATTACHMENT 2K-1 FOOD SERVICE EQUIPMENT LIST  
EXECUTION VERSION  
SEPTEMBER 9, 2022**

Appendix 2K-1 Food Service Equipment List  
 Updated January 24, 2022

ID	Category	Department Room Reference	Total Qty	Item Ref No	Item Description	Long Description	Item Status	Mounting	Max Weight (kg)	Ship Weight (kg)	Width (mm)	Depth (mm)	Height (mm)	Volts	Amps	Hz	Watts	Plug Type	BTU/hr	Dedicated Circuit	Tech Connection (data)	Emergency Power	Water - Cold	Water - Hot	Water - Treated	Steam	Drain	Vent	Gas	Vacuum Dental	Vacuum Med	Compressed Air	Item Notes	Sample Manufacturer 1	Sample Model 1	Sample Manufacturer 2	Sample Manufacturer 3	
CDH OS-TL-05 ID 1	ME	Department Receiving	1	05.01.01	Stainless steel hand sink	Hand Sink, pedestal mounted base, 13-1/2" wide x 9-3/4" front-to-back x 6-3/4" deep bowl, 304 stainless steel construction, splash mount gooseneck spout, pedal valves, P-Trap, tall piece, basket drain, deep-draw stainless design-positive drain, inverted "U" edge NSF. Antimicrobial finish on bowl only. Emergency Eye Wash Unit, faucet-mount, fits in place of aerator on spout. (2) dust covers, pull valve activates fountain, polished chrome finish. Anti-Scald Valve, for emergency eye wash, 1/2" NPT, 65°-95°F (meets ANSI Z358.1 & ASSE 1017 standards). Left & right side splashes.	New	Wall	14.5	14.5	376	480	1019	No	No	No	No	No	No	No	No	No	No	13	13	No	No	38	Yes	No	No	No	No	Hands free operation with eye wash.	Eagle	HSA-10-FA-P	Advance Tabco	Custom Fabricated
CDH OS-TL-05 ID 1	A	Department Receiving	1	05.01.02	Platform cart	Platform Truck, 24"W x 57"D x 33"H, 2000 lbs capacity, removable high end handle, steel construction, powder coat finish. (2) 8" x 8" x 2" casters, (2) 4" casters. NSF rated. Corner Bumpers (set of 2).	New	Mobile	46	46	610	1270	889	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	Steel construction.	Charnal Manufacturing	PT2448	Hatch	Custom Fabricated
CDH OS-TL-05 ID 1	A	Department Receiving	2	05.01.03	Utility cart	Utility Cart, 33" x 18" x 34", 1800 lbs capacity, (3) shelves smooth surface, handles, open sides, plastic construction, brushed aluminum uprights, (4) 4" swivel casters, assembly required, black.	New	Mobile	14	14	473	854	959	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	Plastic Construction	Rubbermaid	FG3424888LA	Metro	Cambro	
CDH OS-TL-05 ID 2	A	Dry Stores Room	2	05.02.01	High density shelving system	High Density Storage System, stationary intermediate unit kit, includes: posts & hardware, epoxy-coated corrosion-resistant finish with antimicrobial protection. Complete with adjustable construction of steel with removable polypropylene overlays or polyester, thermoplastic/polypropylene construction. Construction to be corrosion resistant and coated with anti-microbial substance. Minimum dimensions to be 610mm wide x 1220mm long. All units to include cart washable casters, two locking. Minimum four tiers of shelves. Shelves to be adjustable. Overall dimension of unit to vary depending on the layout of the room. Typically 1220mm or 1524mm wide.	New	Floor	Custom	Custom	Custom	Custom	Custom	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	Plastic Construction	Metro	Max Q	Cambro		
CDH OS-TL-05 ID 2	A	Dry Stores Room	6	05.02.02	Shelving unit	Constructed of steel with removable polypropylene overlays or polyester, thermoplastic/polypropylene construction. Construction to be corrosion resistant and coated with anti-microbial substance. Minimum dimensions to be 610mm wide. All units to include cart washable casters, two locking. Minimum four tiers of shelves. Shelves to be adjustable. Overall dimension of unit to vary depending on the layout of the room. Typically 1220mm or 1524mm wide.	New	Mobile	5	5	610	Varies based on layout - typically 1220mm to 1524mm	1752	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	Plastic Construction	Metro	Max Q	Cambro	
CDH OS-TL-05 ID 3	ME	Refrigerated Store Room	4	05.03.01	Pre-fabricated insulated wall and ceiling panels and refrigeration system	ULC listed pre-fabricated insulated wall and ceiling panels, 4" (100mm) thick with polyurethane insulation. Panels to have a tongue and groove configuration and fastened together with a mechanical cam-lock fastener. Finish to be stainless steel. Rooms complete with 1220mm sliding doors complete with crash double acting insulated doors complete with viewing. All rooms complete with LED light fixtures to provide 50 foot candle lighting levels. Stainless steel head plates on all exposed exterior.	New	Floor	Custom	Custom	Custom	Custom	Custom	1201	15	60	No	Direct	No	Yes	No	No	No	No	No	No	No	No	No	No	No	No	Custom Fabricated Panel Construction	Norbec	Custom	Canadian Curtis	Masterbuilt	
CDH OS-TL-05 ID 3	ME	Refrigerated Store Room	4	05.03.02	Refrigeration evaporator coil	Sized and balanced to match the compressor(s) and must be capable of maintaining internal room temperature (max. +3C for coolers, min. -18C for freezers) while considering humidity levels of surrounding areas, product type and load, heat infiltration and temperature of incoming product. Corrosion free assembly. Time initiated air defrost cycles for coolers. Electric or hot gas defrost for freezers.	New	Floor	Custom	Custom	Custom	Custom	Custom	1201	15	60	No	Direct	No	Yes	No	No	No	No	No	No	No	No	No	No	No	No	Custom Fabricator	Norbec	Custom	Canadian Curtis	Masterbuilt	
CDH OS-TL-05 ID 3	ME	Refrigerated Store Room	4	05.03.03	Refrigeration condensing unit	Remote Water Cooled Sool Condensing unit sized to suit walk-in room size. Unit to include mounting on top of the room. Rack design refrigeration system would be considered if it can be accommodated within the design.	New	Floor	Custom	Custom	Custom	Custom	Custom	2083	20	60	No	Direct	No	Yes	No	No	No	No	No	No	No	No	No	No	No	No	Custom Fabricator	Norbec	Custom	Canadian Curtis	Masterbuilt	
CDH OS-TL-05 ID 3	ME	Refrigerated Store Room	4	05.03.04	Temperature Alarm	High density shelving system, stationary intermediate unit kit, includes: posts & hardware, epoxy-coated corrosion-resistant finish with antimicrobial protection. Complete with adjustable construction of steel with removable polypropylene overlays or polyester, thermoplastic/polypropylene construction. Construction to be corrosion resistant and coated with anti-microbial substance. Minimum dimensions to be 610mm wide x 1220mm long. All units to include cart washable casters, two locking. Minimum four tiers of shelves. Shelves to be adjustable. Overall dimension of unit to vary depending on the layout of the room. Typically 1220mm or 1524mm wide.	New	Floor	Custom	Custom	Custom	Custom	Custom	1201	15	60	No	Direct	No	Yes	Yes	No	No	No	No	No	No	No	No	No	No	No	No	Custom Fabricator	Norbec	Custom	Canadian Curtis	Masterbuilt
CDH OS-TL-05 ID 3	A	Refrigerated Store Room	2	05.03.05	High density shelving system	High Density Storage System, stationary intermediate unit kit, includes: posts & hardware, epoxy-coated corrosion-resistant finish with antimicrobial protection. Complete with adjustable construction of steel with removable polypropylene overlays or polyester, thermoplastic/polypropylene construction. Construction to be corrosion resistant and coated with anti-microbial substance. Minimum dimensions to be 610mm wide x 1220mm long. All units to include cart washable casters, two locking. Minimum four tiers of shelves. Shelves to be adjustable. Overall dimension of unit to vary depending on the layout of the room. Typically 1220mm or 1524mm wide.	New	Floor	Custom	Custom	Custom	Custom	Custom	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	Plastic Construction	Metro	Max Q	Cambro		
CDH OS-TL-05 ID 3	A	Refrigerated Store Room	24	05.03.06	Shelving unit	Constructed of steel with removable polypropylene overlays or polyester, thermoplastic/polypropylene construction. Construction to be corrosion resistant and coated with anti-microbial substance. Minimum dimensions to be 610mm wide. All units to include cart washable casters, two locking. Minimum four tiers of shelves. Shelves to be adjustable. Overall dimension of unit to vary depending on the layout of the room. Typically 1220mm or 1524mm wide.	New	Mobile	5	5	610	Varies based on layout - typically 1220mm to 1524mm	1752	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	Plastic Construction	Metro	Max Q	Cambro		
CDH OS-TL-05 ID 3	A	Refrigerated Store Room	8	05.03.07	Angle racks	Tray Rack, mobile, end load, single section, pass-thru, 20"W x 63-1/4"H, 23"D, pass-thru, closed sides, with sides for (18) 15" x 20" or (18) 16" x 22" trays, slides on 3" casters, riveted aluminum construction, NSF. Continuous Bumper, gray. Mobile Tray Rack Pan stop.	New	Mobile	10	10	510	670	1606	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	Steel construction.	Metro	RD15N	Hatch	Custom Fabricated	
CDH OS-TL-05 ID 4	ME	Frozen Store Room	21	05.04.01	Pre-fabricated insulated wall and ceiling panels and refrigeration system	ULC listed pre-fabricated insulated wall and ceiling panels, 4" (100mm) thick with polyurethane insulation. Panels to have a tongue and groove configuration and fastened together with a mechanical cam-lock fastener. Finish to be stainless steel. Rooms complete with 1220mm sliding doors complete with crash double acting insulated doors complete with viewing. All rooms complete with LED light fixtures to provide 50 foot candle lighting levels. Stainless steel head plates on all exposed exterior.	New	Floor	Custom	Custom	Custom	Custom	Custom	1201	15	60	No	Direct	No	Yes	No	No	No	No	No	No	No	No	No	No	No	No	Custom Fabricated Panel Construction	Norbec	Custom	Canadian Curtis	Masterbuilt	
CDH OS-TL-05 ID 4	ME	Frozen Store Room	21	05.04.02	Refrigeration evaporator coil	Sized and balanced to match the compressor(s) and must be capable of maintaining internal room temperature (max. +3C for coolers, min. -18C for freezers) while considering humidity levels of surrounding areas, product type and load, heat infiltration and temperature of incoming product. Corrosion free assembly. Time initiated air defrost cycles for coolers. Electric or hot gas defrost for freezers.	New	Floor	Custom	Custom	Custom	Custom	Custom	1201	15	60	No	Direct	No	Yes	No	No	No	No	No	No	No	No	No	No	No	No	Custom Fabricator	Norbec	Custom	Canadian Curtis	Masterbuilt	
CDH OS-TL-05 ID 4	ME	Frozen Store Room	21	05.04.03	Refrigeration condensing unit	Remote Water Cooled Sool Condensing unit sized to suit walk-in room size. Unit to include mounting on top of the room. Rack design refrigeration system would be considered if it can be accommodated within the design.	New	Floor	Custom	Custom	Custom	Custom	Custom	2083	20	60	No	Direct	No	Yes	No	No	No	No	No	No	No	No	No	No	No	No	Custom Fabricator	Norbec	Custom	Canadian Curtis	Masterbuilt	
CDH OS-TL-05 ID 4	ME	Frozen Store Room	21	05.04.04	Temperature Alarm	High density shelving system, stationary intermediate unit kit, includes: posts & hardware, epoxy-coated corrosion-resistant finish with antimicrobial protection. Complete with adjustable construction of steel with removable polypropylene overlays or polyester, thermoplastic/polypropylene construction. Construction to be corrosion resistant and coated with anti-microbial substance. Minimum dimensions to be 610mm wide x 1220mm long. All units to include cart washable casters, two locking. Minimum four tiers of shelves. Shelves to be adjustable. Overall dimension of unit to vary depending on the layout of the room. Typically 1220mm or 1524mm wide.	New	Floor	Custom	Custom	Custom	Custom	Custom	1201	15	60	No	Direct	No	Yes	Yes	No	No	No	No	No	No	No	No	No	No	No	No	Custom Fabricator	Norbec	Custom	Canadian Curtis	Masterbuilt
CDH OS-TL-05 ID 4	A	Frozen Store Room	24	05.04.05	Shelving unit	Constructed of steel with removable polypropylene overlays or polyester, thermoplastic/polypropylene construction. Construction to be corrosion resistant and coated with anti-microbial substance. Minimum dimensions to be 610mm wide. All units to include cart washable casters, two locking. Minimum four tiers of shelves. Shelves to be adjustable. Overall dimension of unit to vary depending on the layout of the room. Typically 1220mm or 1524mm wide.	New	Mobile	5	5	610	Varies based on layout - typically 1220mm to 1524mm	1752	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	Plastic Construction	Metro	Max Q	Cambro	
CDH OS-TL-05 ID 4	A	Frozen Store Room	42	05.04.06	Angle racks	Tray Rack, mobile, end load, single section, pass-thru, 20"W x 63-1/4"H, 23"D, pass-thru, closed sides, with sides for (18) 15" x 20" or (18) 16" x 22" trays, slides on 3" casters, riveted aluminum construction, NSF. Continuous Bumper, gray. Mobile Tray Rack Pan stop.	New	Mobile	10	10	510	670	1606	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	Steel construction.	Metro	RD15N	Hatch	Custom Fabricated	
CDH OS-TL-05 ID 37	ME	Frozen Store Room	1	05.04.01	Pre-fabricated insulated wall and ceiling panels and refrigeration system	ULC listed pre-fabricated insulated wall and ceiling panels, 4" (100mm) thick with polyurethane insulation. Panels to have a tongue and groove configuration and fastened together with a mechanical cam-lock fastener. Finish to be stainless steel. Rooms complete with 1220mm sliding doors complete with crash double acting insulated doors complete with viewing. All rooms complete with LED light fixtures to provide 50 foot candle lighting levels. Stainless steel head plates on all exposed exterior.	New	Floor	Custom	Custom	Custom	Custom	Custom	1201	15	60	No	Direct	No	Yes	No	No	No	No	No	No	No	No	No	No	No	No	Custom Fabricated Panel Construction	Norbec	Custom	Canadian Curtis	Masterbuilt	
CDH OS-TL-05 ID 37	ME	Frozen Store Room	1	05.04.02	Refrigeration evaporator coil	Sized and balanced to match the compressor(s) and must be capable of maintaining internal room temperature (max. +3C for coolers, min. -18C for freezers) while considering humidity levels of surrounding areas, product type and load, heat infiltration and temperature of incoming product. Corrosion free assembly. Time initiated air defrost cycles for coolers. Electric or hot gas defrost for freezers.	New	Floor	Custom	Custom	Custom	Custom	Custom	1201	15	60	No	Direct	No	Yes	No	No	No	No	No	No	No	No	No	No	No	No	Custom Fabricator	Norbec	Custom	Canadian Curtis	Masterbuilt	
CDH OS-TL-05 ID 37	ME	Frozen Store Room	1	05.04.03	Refrigeration condensing unit	Remote Water Cooled Sool Condensing unit sized to suit walk-in room size. Unit to include mounting on top of the room. Rack design refrigeration system would be considered if it can be accommodated within the design.	New	Floor	Custom	Custom	Custom	Custom	Custom	2083	20	60	No	Direct	No	Yes	No	No	No	No	No	No	No	No	No	No	No	No	Custom Fabricator	Norbec	Custom	Canadian Curtis	Masterbuilt	
CDH OS-TL-05 ID 37	ME	Frozen Store Room	1	05.04.04	Temperature Alarm	High density shelving system, stationary intermediate unit kit, includes: posts & hardware, epoxy-coated corrosion-resistant finish with antimicrobial protection. Complete with adjustable construction of steel with removable polypropylene overlays or polyester, thermoplastic/polypropylene construction. Construction to be corrosion resistant and coated with anti-microbial substance. Minimum dimensions to be 610mm wide x 1220mm long. All units to include cart washable casters, two locking. Minimum four tiers of shelves. Shelves to be adjustable. Overall dimension of unit to vary depending on the layout of the room. Typically 1220mm or 1524mm wide.	New	Floor	Custom	Custom	Custom	Custom	Custom	1201	15	60	No	Direct	No	Yes	Yes	No	No	No	No	No	No	No	No	No	No	No	No	Custom Fabricator	Norbec	Custom	Canadian Curtis	Masterbuilt
CDH OS-TL-05 ID 37	A	Frozen Store Room	8	05.04.05	Shelving unit	Constructed of steel with removable polypropylene overlays or polyester, thermoplastic/polypropylene construction. Construction to be corrosion resistant and coated with anti-microbial substance. Minimum dimensions to be 610mm wide. All units to include cart washable casters, two locking. Minimum four tiers of shelves. Shelves to be adjustable. Overall dimension of unit to vary depending on the layout of the room. Typically 1220mm or 1524mm wide.	New	Mobile	5	5	610	Varies based on layout - typically 1220mm to 1524mm	1752	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	Plastic Construction	Metro	Max Q	Cambro	
CDH OS-TL-05 ID 37	A	Frozen Store Room	2	05.04.06	Angle racks	Tray Rack, mobile, end load, single section, pass-thru, 20"W x 63-1/4"H, 23"D, pass-thru, closed sides, with sides for (18) 15" x 20" or (18) 16" x 22" trays, slides on 3" casters, riveted aluminum construction, NSF. Continuous Bumper, gray. Mobile Tray Rack Pan stop.	New	Mobile	10	10	510	670	1606	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	Steel construction.	Metro	RD15N	Hatch	Custom Fabricated	
CDH OS-TL-05 ID 5	A	Issue and Ingredient Control Room	1	05.05.01	Stainless steel table	Stainless steel construction, type 304, #4 finish. Length to suit design x 760mm wide x 84mm high, stainless steel top with stainless steel or galvanized steel sub-top. Hair channel reinforcement to be stainless steel or galvanized steel on centre. Legs to be stainless steel, tubing or square welded to subtop. Stainless steel cross bracing as required. Sound deadening as required. 4 all swivel non-marking rubber cast-washable casters with brakes, 5.5" casters.	New	Floor										Plug	No	Yes	No	No	No	No	No	No	No	No	No	No	No	No	Steel construction.	Custom Fabricated	Custom Fabricated			
CDH OS-TL-05 ID 5	ME	Issue and Ingredient Control Room	1	05.05.02	Stainless steel overshelf	Stainless steel construction, type 304, #4 finish. Length to suit design x 300mm wide x 150mm high, stainless steel top with stainless steel or galvanized steel sub-top. Hair channel reinforcement to be stainless steel or galvanized steel on centre.	New	Wall													No	No	No	No	No	No	No	No	No	No	No	No	Steel construction.	Custom Fabricated	Custom Fabricated			
CDH OS-TL-05 ID 5	ME	Issue and Ingredient Control Room	1	05.05.03	Stainless steel hand sink	Hand Sink, pedestal mounted base, 13-1/2" wide x 9-3/4" front-to-back x 6-3/4" deep bowl, 304 stainless steel construction, splash mount gooseneck spout, pedal valves, P-Trap, tall piece, basket drain, deep-draw stainless design-positive drain, inverted "U" edge NSF. Antimicrobial finish on bowl only. Emergency Eye Wash Unit, faucet-mount, fits in place of aerator on spout. (2) dust covers, pull valve activates fountain, polished chrome finish. Anti-Scald Valve, for emergency eye wash, 1/2" NPT, 65°-95°F (meets ANSI Z358.1 & ASSE 1017 standards). Left & right side splashes.	New	Wall	14.5	14.5	376	480	1019	No	No	No	No	No	No	No	No	No	No	13	13	No	No	38	Yes	No	No	No	No	Hands free operation with eye wash.	Eagle	HSA-10-FA-P	Advance Tabco	Custom Fabricated
CDH OS-TL-05 ID 5	A	Issue and Ingredient Control Room	8	05.05.04	Ingredient Bins	Ingredient Bin, 4-18 cu. ft, 18"W x 29-3/4"D x 28"H, mobile, slant front with sliding lid, 32 cu. scoop, seamless construction. 3" extra wide casters front head & rear axle, white base/clear lid. USDA, FDA, NSF.	New	Mobile													No	No	No	No	No	No	No	No	No	No	No	No	Plastic Construction	Rubbermaid	SMFG360389H7	Cambro		
CDH OS-TL-05 ID 5	A	Issue and Ingredient Control Room	1	05.05.05	Digital Scale	Digital Scale, 20 lb. capacity in 0.2 increments. 7" x 7" removable stainless steel platform. LCD display, built-in calibration, features On/Tare, Mode/Calibrate, zero, automatic Off, and Off function, includes AC adaptor and protective cover. 9VAC, can use (2) AA Batteries, OUL, NSF, CE.	New	On stainless steel table			254	254	76.2	1201	10	60	No	Plug	No	Yes	No	No	No	No	No	No	No	No	No	No	No	No	Mobile	Eduind	BRV-320	Globe	Hobart	
CDH OS-TL-05 ID 5	A	Issue and Ingredient Control Room	1	05.05.06	Can opener, electrical	Can Opener, electric, 2-speed (Silver model is rated for opening smaller cans), recommended usage up to 75 cans per day, 11.5x5.5x3.5. Replacement Parts Kit.	New	On stainless steel table													Yes	No	No	No	No	No	No	No	No	No	No	Mobile	Eduind	203	Globe	Hobart		
CDH OS-TL-05 ID 5	A	Issue and Ingredient Control Room	1	05.05.07	Shelving unit	Constructed of steel with removable polypropylene overlays or polyester, thermoplastic/polypropylene construction. Construction to be corrosion resistant and coated with anti-microbial substance. Minimum dimensions to be 610mm wide. All units to include cart washable casters, two locking. Minimum four tiers of shelves. Shelves to be adjustable. Overall dimension of unit to vary depending on the layout of the room. Typically 1220mm or 1524mm wide.	New	Mobile	5	5	610	Varies based on layout - typically 1220mm to																										

**Appendix 2K-1 Food Service Equipment List**  
 Updated January 24, 2022

ID	Category	Department Room Reference	Total Qty	Item Ref No	Item Description	Long Description	Item Status	Mounting	Max Weight (kg)	Ship Weight (kg)	Width (mm)	Depth (mm)	Height (mm)	Volts	Amps	Hz	Watts	Plug Type	BTU/hr	Dedicated Circuit	Tech Connection (data)	Emergency Power	Water - Cold	Water - Hot	Water - Treated	Steam	Drain	Vent	Gas	Vacuum-Dental	Vacuum-Med	Compressed Air	Item Notes	Sample Manufacturer 1	Sample Model 1	Sample Manufacturer 2	Sample Manufacturer 3		
CDH-OS-TL-05 ID 1	ME	Preparation and Portioning	2	05.07.01	Stainless steel table with sink	Stainless steel construction, type 304, #4 finish, length to suit design x 760mm wide x 864mm high, stainless steel top with 2.0mm stainless steel or galvanized steel sub-top, Hat channel reinforcement to be stainless steel or galvanized steel on centre. Sinks to be minimum 18" x 12" deep complete with hot and cold water faucet with swing spout, Legs to be stainless steel, tubing or square welded to subtop, Stainless steel cross bracing as required. Sound deadening as required. Backsplash to include radius covered corner, sprayed to wall where required. Bullet feet for tables without mix services, flanged feet secured to floor with s.s. fasteners for tables with mix services, S.S. drawers.	New	Floor			762	864	1201	15	60	No	No	No	Plug	No	No	No	No	13	13	No	38	No	No	No	No	No	Steel construction	Custom Fabricated	Custom Fabricated				
CDH-OS-TL-05 ID 7	A	Preparation and Portioning	2	05.07.02	Stainless steel mobile work table	Stainless steel construction, type 304, #4 finish, length to suit design x 760mm wide x 864mm high, stainless steel top with stainless steel or galvanized steel sub-top, Hat channel reinforcement to be stainless steel or galvanized steel on centre, Legs to be stainless steel, tubing or square welded to subtop, Stainless steel cross bracing as required. Sound deadening as required. 4 all swivel non-marking rubber cast-washable casters with brakes, S.S. drawers.	New	Mobile			762	864	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	Steel construction	Custom Fabricated	Custom Fabricated					
CDH-OS-TL-05 ID 7	A	Preparation and Portioning	1	05.07.03	Stainless steel table	Stainless steel construction, type 304, #4 finish, length to suit design x 760mm wide x 864mm high, stainless steel top with stainless steel or galvanized steel sub-top, Hat channel reinforcement to be stainless steel or galvanized steel on centre, Legs to be stainless steel, tubing or square welded to subtop, Stainless steel cross bracing as required. Sound deadening as required. 4 all swivel non-marking rubber cast-washable casters with brakes, S.S. drawers.	New	Floor			762	864	1201	15	60	No	No	No	Plug	No	No	No	No	No	No	No	No	No	No	No	No	Steel construction	Custom Fabricated	Custom Fabricated					
CDH-OS-TL-05 ID 7	ME	Preparation and Portioning	3	05.07.04	Stainless steel overshelf	Stainless steel construction, type 304, #4 finish, length to suit design x 300mm wide x 150mm high, stainless steel top with stainless steel or galvanized steel sub-top, Hat channel reinforcement to be stainless steel or galvanized steel on centre.	New	Wall				304.8	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	Steel construction	Custom Fabricated	Custom Fabricated						
CDH-OS-TL-05 ID 7	A	Preparation and Portioning	5	05.07.05	Waste bin with duty	Container, round, open type, 20-gallon capacity, high-impact plastic construction, grey. Lid, round, for 20 gallon container, blue. Duty, for containers, black.	New	Mobile						No	No	No	No	No	No	No	Yes	No	No	No	No	No	No	No	No	No	Plastic Construction	Rubbermaid	Brute 2620						
CDH-OS-TL-05 ID 7	A	Preparation and Portioning	1	05.07.06	Counter slicer w/ Mobile Stand	Heavy Duty Meat Slicer, automatic, 13" CleanCut™ removable knife & tool, anodized finish with (6) interlocks, (3) stroke lengths & (4) stroke speeds, removable meat grip assembly, removable ring guard cover, product fence, single action top mounted parameter with bronze™ stones, manual lift lever, 12/16 motor, 120V/60Hz/1ph NSF CETLus. Standard warranty - 1 Year limited warranty. Food chute for HS series slicers. Product fence for HS series slicers. Product deflector for HS series slicers.	New	Mobile Stand			326	362	635	1201	15	60	No	No	No	Plug	No	No	No	No	No	No	No	No	No	No	No	Steel construction	Hobart	H59-1	Globe				
CDH-OS-TL-05 ID 7	A	Preparation and Portioning	1	05.07.07	Mobile Stand	Mobile stand to be stainless steel construction, type 304, #4 finish, stainless steel top with stainless steel or galvanized steel sub-top, Hat channel reinforcement to be stainless steel or galvanized steel on centre, Legs to be stainless steel, tubing or square welded to subtop, Stainless steel cross bracing as required. Sound deadening as required. 4 all swivel non-marking rubber cast-washable casters with brakes.	New	Floor			610	610	610	No	No	No	No	No	No	Yes	No	No	No	No	No	No	No	No	No	No	Steel construction	Custom Fabricated	Aero 4MSU-2424						
CDH-OS-TL-05 ID 7	A	Preparation and Portioning	1	05.07.08	Floor Mixer	Mixer - Unit Only, 2.7 HP, 60 quart capacity, four fixed speeds, gear transmission, 20 min. timer, taper attachment hub, power bowl fit, stainless steel bowl guard, 200-240/50/60Hz, Mixer Bowl, 60 quart stainless steel. Max 60 oz. 12" flat beater, aluminum. Mixer 60 quart 17" wide, stainless steel. 60 oz. 12" straight dough arm, aluminum. Mixer Bowl Truck, aluminum, for 60 quart mixers.	New	Floor			1223	1033	1557	2083	10	60	No	No	Direct	No	No	No	No	No	No	No	No	No	No	No	No	Steel construction	Hobart	HL600	Globe				
CDH-OS-TL-05 ID 7	A	Preparation and Portioning	3	05.07.09	Mixer/Blender	Commercial blender/mixer, variable speed, stainless steel body with handle, stainless steel 10" serrated blade assembly, on/off buttons, pulse button, variable speed 370 - 3450 RPM, 120V/60Hz/1ph, 11 amps, 2 HP, NEMA 5-15P, ETL, electrical & sanitation, cETL, UL, NSF, CAN/CSA. Stainless steel bowl. "2" Blade, fine particle.	New	On stainless steel table			300	152	609	1201	15	60	No	No	No	No	Yes	No	No	No	No	No	No	No	No	No	No	Steel construction	Robot Coup	Blender 404G	Globe				
CDH-OS-TL-05 ID 7	A	Preparation and Portioning	2	05.07.10	Can opener, electrical	Can Opener, electric, 2-speed (lower speed is best for opening smaller cans), recommended usage up to 75 cans per day, 115V/60Hz/1ph. Replacement Parts Kit.	New	On stainless steel table						1201	15	60	No	No	Plug	No	Yes	No	No	No	No	No	No	No	No	No	No	No	Mobile	Edlund	203	Globe	Hobart		
CDH-OS-TL-05 ID 7	A	Preparation and Portioning	1	05.07.11	Reach-In Freezer	Freezer, Reach-In, Two-Compartment, self-contained refrigeration, stainless steel exterior and interior, shallow depth, wide full-height doors, microprocessor control, unit can be programmed to operate at -10 degrees Fahrenheit, cULus, NSF, 3 years parts & labor, 5 year compressor warranty, 0 degree Fahrenheit holding temperature, standard, 115V/60Hz/1ph, 6.0 amps, with cord & NEMA 5-15P standard. Top mounted electric condensate evaporator. Stainless steel back with rear louvers. Casters, 6" high locking (set of 4).	New	Floor			1337-664	864	2386	1201	10	60	No	No	No	No	No	Yes	No	No	No	No	No	No	No	No	No	Mobile	True Manufacturing	STAR2-2S-HC	Trailen	Randell			
CDH-OS-TL-05 ID 7	ME	Preparation and Portioning	1	05.07.12	Stainless steel hand sink	Hand Sink, pedestal mounted base, 13-1/2" wide x 9-3/4" front-to-back x 6-3/4" deep bowl, 304 stainless steel construction, splash mount gooseneck spout, pedal valves, P-trap, tail piece, ballast drain, deep-draw seamless design-podiathe drain, inverted "V" edge, NSF. Antimicrobial finish on bowl only. Emergency Eye Wash Unit, faucet-mount, fits in place of aerator on spout, (2) dust covers, pull valve activates fountain, polished chrome finish. Anti-Scald Valve, for emergency eye wash, 1/2" NPT, 65°-95°F (meets ANSI Z358.1 & ASSE 1017 standards). Left & right side splashes.	New	Wall	14.5	14.5	376	480	1019	No	No	No	No	No	No	No	No	No	No	No	13	13	No	38	Yes	No	No	No	No	Hands free operation with eye wash.	Eagle	HSA-10-FA-P	Advance Tabco	Custom Fabricated	
CDH-OS-TL-05 ID 8	ME	Nourishments and Special Diets	1	05.08.01	Stainless steel table with sink	Stainless steel construction, type 304, #4 finish, length to suit design x 760mm wide x 864mm high, stainless steel top with 2.0mm stainless steel or galvanized steel sub-top, Hat channel reinforcement to be stainless steel or galvanized steel on centre. Sinks to be minimum 18" x 12" deep complete with hot and cold water faucet with swing spout, Legs to be stainless steel, tubing or square welded to subtop, Stainless steel cross bracing as required. Sound deadening as required. Backsplash to include radius covered corner, sprayed to wall where required. Bullet feet for tables without mix services, flanged feet secured to floor with s.s. fasteners for tables with mix services, S.S. drawers.	New	Floor			762	864	1201	15	60	No	No	No	No	Plug	No	No	No	13	13	No	38	No	No	No	No	No	Steel construction	Custom Fabricated	Custom Fabricated				
CDH-OS-TL-05 ID 8	A	Nourishments and Special Diets	2	05.08.02	Digital Scale	Digital Scale, 20 lb, capacity 0.2 increments, 7" x 7" removable stainless steel platform, LCD display, field calibratable, features On/Off, Mode/Calibrate, zero, automatic Off, and Off function, includes AC adapter and protective cover. 9VAC, con (2) AA batteries, 60V, NSF, CE.	New	On stainless steel table			254	254	76.2	1201	10	60	No	No	Plug	No	Yes	No	No	No	No	No	No	No	No	No	No	Mobile	Edlund	BRV-320	Globe	Hobart			
CDH-OS-TL-05 ID 8	A	Nourishments and Special Diets	1	05.08.03	Reach-in refrigerator	Spec-Line Refrigerator, Reach-In, Two-Section, self-contained refrigeration, stainless steel exterior and interior, standard depth, full-height door, microprocessor controls, 6" adjustable stainless steel legs, 1/3 HP, cULus, NSF, 3 years parts & labor, 5 year compressor warranty, standard, 115V/60Hz/1ph, 8.0 amps, with cord & NEMA 5-15P standard. Door hinged on right standard. NAFEM data protocol gateway (access up to four units). Stainless steel back with rear louvers. Casters, 6" high locking (set of 4).	New	Floor			1650	864	2286	1201	20	60	No	No	No	Plug	No	No	No	No	No	No	No	No	No	No	No	Mobile	True Manufacturing	STAR2-2S-HC	Trailen	Randell			
CDH-OS-TL-05 ID 8	A	Nourishments and Special Diets	2	05.08.04	Waste bin with duty	Container, round, open type, 20-gallon capacity, high-impact plastic construction, grey. Lid, round, for 20 gallon container, blue. Duty, for containers, black.	New	Mobile						No	No	No	No	No	No	No	Yes	No	No	No	No	No	No	No	No	No	No	Plastic Construction	Rubbermaid	Brute 2620					
CDH-OS-TL-05 ID 8	ME	Nourishments and Special Diets	1	05.08.05	Stainless steel hand sink	Hand Sink, pedestal mounted base, 13-1/2" wide x 9-3/4" front-to-back x 6-3/4" deep bowl, 304 stainless steel construction, splash mount gooseneck spout, pedal valves, P-trap, tail piece, ballast drain, deep-draw seamless design-podiathe drain, inverted "V" edge, NSF. Antimicrobial finish on bowl only. Emergency Eye Wash Unit, faucet-mount, fits in place of aerator on spout, (2) dust covers, pull valve activates fountain, polished chrome finish. Anti-Scald Valve, for emergency eye wash, 1/2" NPT, 65°-95°F (meets ANSI Z358.1 & ASSE 1017 standards). Left & right side splashes.	New	Wall	14.5	14.5	376	480	1019	No	No	No	No	No	No	No	No	No	No	13	13	No	38	Yes	No	No	No	No	Hands free operation with eye wash.	Eagle	HSA-10-FA-P	Advance Tabco	Custom Fabricated		
CDH-OS-TL-05 ID 8	ME	Main Cooking (including Bakery)	2	05.09.01	Exhaust hood with fire protection system	The hood shall be designed with Side-Jet technology to reduce the exhaust airflow rate required, and to improve the capture and containment efficiency of the hood, while reducing energy consumption. The Side-Jet technology shall be introduced through a special discharge panel and shall not exceed 10% of the calculated exhaust airflow. The Side-Jet technology discharge velocity will be a minimum of 1500 feet per minute. Side or grille type discharge shall not be used. The Side-Jet technology shall be internally mounted with a speed control and will not require a fire damper or electronic shut down in fire mode. The integral front discharge panel or air plenum shall be manufactured of the same material as the hood. The floor of the plenum will be perforated stainless steel to deliver low velocity air to the space and to minimize room turbulence while refreshing the occupied zone. The SPFF fire suppression system is an industry leader in rugged components and superior fire suppression. The versatile SPFF system incorporates a stored pressure cylinder and delivers a wet chemical agent to a fire, quickly suppressing and containing fires in a wide variety of applications. Hood can be supplied in multiple sections to fit in the building. Hoods can be installed back to back.	New	Ceiling			See Long Description	See Long Description	See Long Description	2 @ 1201	20	60	No	No	No	No	No	Direct	No	Yes	No	No	No	No	No	No	No	No	No	No	CFM T.B.C. Type I Hood	Hallon	KVE	Spring Air	Gaylord
CDH-OS-TL-05 ID 9	A	Main Cooking (including Bakery)	2	05.09.02	Combination steam convection oven, electric -20 GN capacity	Combo Oven/Steamer, electric, (20) 18" x 26" full size sheet or (40) 12" x 20" full size hotel pan capacity. Control with 7 modes. Control, Efficient Care/Control, Combo-Steamer with 3 modes, core temp probe with 6 point measurement, hand shower with automatic retracting system, mobile oven rack included, (10) grid shelves, ethernet interface, 208/60/3-ph, 189.0 amps, 68.0 kW (dual voltage, retrofittable to 240V/60/3-ph, 218.0 amps, 68.0 kW), 2 years parts and labor, 5 years steam generator warranty. Manufacturer Technical Start-Up, electric units, by an authorized Service Company. Water Filtration Double Cartridge System, for Combo-Oven if used for more than 2 units includes: (1) double head with pressure gauge, (2) filter & (1) filter installation kit for each additional unit add (1) additional head & additional cartridge. Maximum (4) cartridges). The carbon block technology reduces the effects of sediment, chloramines and chlorine while providing the required flow rates. Heat Shield, for left side panel. Unit Connection Kit, includes: water connection hole 1/2" (2) with 3/4" union & DN 50mm (2") unit drain set (8" x HT-bow 87", 2" x HT-bow 45", 4" x HT-PIPE 500mm, 1 x sleeve). Externally attached core temperature probe. Control panel protection. Mobile stand with casters (4) with locks.	New	Floor			1062	1867	1117	2083	189	60	No	No	Direct	No	Yes	No	13	No	13	No	52	No	No	No	No	No	No	No	Steel construction	Rational	SCC 202 E	Conotherm	Budgette
CDH-OS-TL-05 ID 9	A	Main Cooking (including Bakery)	1	05.09.03	Combination steam convection oven, electric -10 GN capacity	Combo Oven/Steamer, electric, (10) 18" x 26" full size sheet or (20) 12" x 20" full size hotel pan capacity. Control with 7 modes. Combo-Steamer with 3 modes, core temp probe with 8 point measurement, hand shower with automatic retracting system, mobile oven rack included, (10) grid shelves, ethernet interface, 208/60/3-ph, 103 amps, 36.0 kW, 2 years parts and labor, 5 years steam generator warranty. Manufacturer Technical Start-Up, electric units, by an authorized Service Company. Water Filtration Double Cartridge System, for Combo-Oven if used for more than 2 units includes: (1) double head with pressure gauge, (2) filter & (1) filter installation kit for each additional unit add (1) additional head & additional cartridge. Maximum (4) cartridges). The carbon block technology reduces the effects of sediment, chloramines and chlorine while providing the required flow rates. Heat Shield, for left side panel. Unit Connection Kit, includes: water connection hole 1/2" (2) with 3/4" union & DN 50mm (2") unit drain set (8" x HT-bow 87", 2" x HT-bow 45", 4" x HT-PIPE 500mm, 1 x sleeve). Externally attached core temperature probe. Control panel protection. Mobile stand with casters (4) with locks.	New	Floor			1067	1037	1042 plus stand	2083	103	60	No	No	Direct	No	Yes	No	13	No	13	No	52	No	No	No	No	No	No	No	Steel construction	Rational	SCC 102 E	Conotherm	Budgette
CDH-OS-TL-05 ID 9	A	Main Cooking (including Bakery)	1	05.09.04	Convection oven	Convection Oven, electric, double-deck, deep depth 43", (2) speed fan. Solid state digital control with Cook It Hold, electric ignition, dependent 60/40 doors with windows, stainless steel front, sides & top, porcelain cavity, 6-1/2" legs. 240V/60/3-ph, NSF, UL, cUL, CE. Stainless steel endcapped, per deck.	New	Floor			965	1828	1067	2 @ 2083	2 @ 30	60	No	No	Direct	No	Yes	No	No	No	No	No	No	No	No	No	No	No	Steel construction	Garland	MCOES-20 4881602	Vulcan	Southbend		
CDH-OS-TL-05 ID 9	A	Main Cooking (including Bakery)	1	05.09.05	Convection steamer	Convection Steamer, electric, ballless, double decked, on equipment stand, (3) full size pan capacity per compartment, Controls, 60-minute electro-mechanical timer & manual (continuous steaming) bypass switch, left hand hinged door, controls on right, automatic drain & water level controls, mounting spacers, 4" adjustable legs, 84 per cavity, UL, cUL, NSF, ENERGY STAR, (2) 208/3 208/60/3-ph, 208 amp, 3-amp, 2-wire, Electronic Timer with Load Compensating Feature, two compartment, 5 Foot (1524mm) FDA Approved National Hose Thread, style water connection kit (garden hose thread), TIVO required. Heat Shield. Water Filter Assembly, for counter top steamers, includes (1) cartridge, (1) filter cartridge, dip tube & scale 7.5-cc, jacket, wall-mounting bracket & gauge assembly.	New	Floor			609	864	1778	2 @ 2083	2 @ 30	60	No	No	Direct	No	No	19	No	19	No	38	No	No	No	No	No	No	No	Steel construction	Cleveland	(2)2CETE 1	Vulcan	Southbend	
CDH-OS-TL-05 ID 9	A	Main Cooking (including Bakery)	1	05.09.06	Kettle (12 gallon)	Steam Jacketed Kettle on stand, electric, 12-gallon capacity, stainless steel exterior finish. Priority boost, with legging & mounting bracket for fitting kettles. Manufacturer stand with deep draw.	New	Floor			584	521	737	2083	30	60	No	No	Direct	No	Yes	No	13	13	No	52	No	No	No	No	No	Steel construction	Cleveland	KEP-12T-STD-28	Southbend	Garland			
CDH-OS-TL-05 ID 9	A	Main Cooking (including Bakery)	2	05.09.07	Kettles (25 gallon)	Short Series Steam Jacketed Kettle, electric, Tilting, 25-gallon capacity, full steam jacket design, 35" rim height, open H-trig base, stainless steel exterior finish, standard with tapered feet, 50 psi rating. 2" straight draw-off valve with strainer. Spring assisted cover (25 gallon). Double Priority Faucet, with swing spout & mounting bracket for fitting kettles. Heat deflector.	New	Floor			1066	965	1625	2083	30	60	No	No	Direct	No	Yes	No	13	13	No	52	No	No	No	No	No	Steel construction	Cleveland	KEL-25T	Southbend	Garland			
CDH-OS-TL-05 ID 9	A	Main Cooking (including Bakery)	2	05.09.08	2 burner range - counter type	Heavy Duty Range, Electric, 12", manual controls, stainless steel front, sides & backguard, 6" adjustable legs, NSF. Complete stainless steel with casters, galvanized wheels (non-marking).	New	Floor						208	1	19	No	Yes	No	No	No	No	No	No	No	No	No	No	No	No	Steel construction	Star	502FF	Vollrath	Vulcan				
CDH-OS-TL-05 ID 9	A	Main Cooking (including Bakery)	3	05.09.09	Rapid cook oven with stand	Commercial grade rapid cook oven complete with type 304 stainless steel interior and removable grease pan, integral incrustating catalytic converter for UL710 listed ventless operation, independently controlled dual motors, external air filtration, and smart menu system. Includes stainless steel equipment stand.	New	Counter			762	660	812	208/240	3	30	No	Yes	No	Yes	No	No	No	No	No	No	No	No	No	No	No	Steel construction	Merry Chef	E4	Turbochef	ACP			
CDH-OS-TL-05 ID 9	ME	Main Cooking (including Bakery)	1	05.09.10	Stainless steel table with sink	Stainless steel construction, type 304, #4 finish, length to suit design x 760mm wide x 864mm high, stainless steel top with 2.0mm stainless steel or galvanized steel sub-top, Hat channel reinforcement to be stainless steel or galvanized steel on centre. Sinks to be minimum 18" x 12" deep complete with hot and cold water faucet with swing spout, Legs to be stainless steel, tubing or square welded to subtop, Stainless steel cross bracing as required. Sound deadening as required. Backsplash to include radius covered corner, sprayed to wall where required. Bullet feet for tables without mix services, flanged feet secured to floor with s.s. fasteners for tables with mix services, S.S. drawers.	New	Floor			762	864	1201	15	60	No	No	No	Yes	No	Yes	No	No	13	13	No	38	No	No	No	No	No	Steel construction	Custom Fabricated	Custom Fabricated				

Appendix 2K-1 Food Service Equipment List  
Updated January 24, 2022

ID	Category	Department Room Reference	Total Qty	Item Ref No	Item Description	Long Description	Item Status	Mounting	Max Weight (kg)	Ship Weight (kg)	Width (mm)	Depth (mm)	Height (mm)	Volts	Amps	Hz	Watts	Plug Type	BTU/hr	Dedicated Circuit	Tech Connection (data)	Emergency Power	Water - Cold	Water - Hot	Water - Treated	Steam	Drain	Vent	Gas	Vacuum Dental	Vacuum Med	Compressed Air	Item Notes	Sample Manufacturer 1	Sample Model 1	Sample Manufacturer 2	Sample Manufacturer 3					
CDH OS-TL-05 ID 9	A	Main Cooking (including Bakery)	1	05.09.11	Stainless steel table with heated over shelf	Stainless steel construction, type 304, #4 finish. Length to suit design x 760mm wide x 864mm high, stainless steel top with 2.0mm stainless steel or galvanized steel sub-top. Hot channel reinforcement to be stainless steel or galvanized steel on centre. Legs to be stainless steel, tubing or square welded to subtop. Stainless steel cross bracing as required. Sound deadening as required. Bullet feet for tables without m/s services, flanged feet secured to floor with a.s. fasteners for tables with m/s services, S.S. drawers. Complete with double over shelf with top section heated from above with heat strips.	New	Floor			Varies based on layout - typically 1524mm to 1828	762	864	2081	10	60	No	Direct	No	No	No	No	13	13	No	No	38	No	No	No	No	No	Steel construction.	Custom Fabricated	Custom Fabricated							
CDH OS-TL-05 ID 9	A	Main Cooking (including Bakery)	1	05.09.12	Stainless steel trench drain	Stainless steel construction, type 304, #4 finish. Length and width to suit design x 150mm deep. All radius corners, 1.5mm stainless steel pan Honeycomb or other patterned grating, removable in sections. Provide strainer at all drains. Positioned at wetlines and fit fry pan. Quantity and size to be confirmed based on final design.	New	Floor			See Long Description	150	See Long Description	No	No	No	No	No	No	No	No	No	No	No	No	No	2 @ 75mm direct to grease trap	No	No	No	No	No	Steel construction.	Custom Fabricated	Custom Fabricated							
CDH OS-TL-05 ID 9	A	Main Cooking (including Bakery)	3	05.09.13	Hot holding cabinet	Low Temperature Holding Cabinet, double compartment, on/off simple control with adjustable thermostats, indicator light, (2) sets of chrome plated universal side rails, (4) sets of top sides, (16) 20" x 2" x 12" full size pan capacity, heavy-duty stainless steel exterior, 5" casters, 2 right, 2 left with brakes, cULus, 208-240V/50/1-ph, 7.0-8.0 amps, 1.4-1.9kW, 2000W, 8 cond, NEMA 6-15P. Solid state electronic control, LED display, six independent multiple timers & probes, handle, push/stop. Solid door, hinged on right, standard. Door lock with key, per door. Bumper, full perimeter (not available with 2-1/2" casters). Casters, 3-1/2" (86mm), stem, 2 right, 2 left with brakes.	New	Mobile						2081	7	60	No	Plug	No	No	No	No	No	No	No	No	No	No	No	No	No	No	Steel construction.	Abt Shaam	1200-UP	FWE		Metro				
CDH OS-TL-05 ID 9	A	Main Cooking (including Bakery)	2	05.09.14	Pot rack	Mobile Pot & Pan Rack, 48"W x 24"D x 68"H, (4) shelves acid embossed stainless steel (2) polyurethane swivel casters & (2) polyurethane swivel casters with brake, NSF.	New	Mobile			Variable	609	1727	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	Plastic Construction.	Metro	PR48ES	Cambro						
CDH OS-TL-05 ID 9	A	Main Cooking (including Bakery)	4	05.09.15	Waste bin with duty	Container, round, open type, 20-gallon capacity, high-impact plastic construction, grey. Lid, round, for 20 gallon container, blue. Duty container, black.	New	Mobile						No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	Plastic Construction.	Rubbermaid	Brute 2620							
CDH OS-TL-05 ID 9	ME	Main Cooking (including Bakery)	1	05.09.16	Stainless steel hand sink	Hand Sink, pedestal mounted base, 13-1/2" wide x 9-3/4" front-to-back x 6-3/4" deep bowl, 304 stainless steel construction, splash mount gooseneck spout, pedal valve, P-trap, tall plate, basket drain, deep-drain seamless design-positive drain, inverted "Y" edge, NSF. Antimicrobial finish on bowl only. Emergency Eye Wash Unit, faucet-mount, fits in place of aerator on spout, (2) dust covers, pull valve activates fountain, polished chrome finish. Anti-Scald Valve, for emergency eye wash, 1/2" NPT, 65-95°F (meets ANSI Z358.1 & ASSE 1017 standards). Left & right side splashplates.	New	Wall				376	480	1019	No	No	No	No	No	No	No	No	No	No	13	13	No	38	Yes	No	No	No	No	Hands free operation with eye wash.	Eagle	HSA-10-FA-P	Advance Tabco		Custom Fabricated			
CDH OS-TL-05 ID 9	A	Main Cooking (including Bakery)	4	05.09.17	Packaging Machine	Vacuum packaging machine. Stainless steel chamber, pump and double 1/8" seal bar providing double seal with electric cut-off. Gas flush to maintain product color and extended shelf life.	New	Mobile	84	111	585	610	445	115/1	21	60		Plug	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	Steel		350D						
CDH OS-TL-05 ID 10	ME	Pot Washing Room	1	05.10.01	Stainless steel pot wash table w/ three compartment sink	Stainless steel construction, type 304, #4 finish. Length to suit design x 760mm wide x 864mm high, 1.5mm stainless steel top with stainless steel or galvanized steel sub-top. Hot channel reinforcement to be stainless steel or galvanized steel on centre, triple Sinks to be minimum 18" x 16" x 12" deep complete with hot and cold water faucet with swing spout for each sink compartment. Legs to be stainless steel, tubing or square welded to subtop. Stainless steel cross bracing as required. Sound deadening as required. Backsplash to include radius corner, applied to wall where required. Bullet feet for tables without m/s services, flanged feet secured to floor with a.s. fasteners for tables with m/s services. Complete with overhead. This is ideally integrated into the table/dish table at the dishwasher. Include removable stainless steel H-shaped apron across all three sinks.	New	Floor			Variable	762	864	2081	10	60	No	Direct	No	No	No	No	No	No	2 @ 13mm	2 @ 13mm	No	No	3 @ 50mm to Grease Trap	No	No	No	No	No	Steel construction.	Custom Fabricated						
CDH OS-TL-05 ID 10	ME	Pot Washing Room	1	05.10.02	Hose reel	3/4" long spray gun with air wand and moulded heat resistant gun. Adjustable spray nozzle for high-low pressure. 6' inlet supply hose. In-line water filter. Stainless steel wall mounted bracket with sturdy shelf. Bypass unloader valve allows unit to idle and moderate. Three inch locking casters and rear wheels designed for wet conditions. Non-marking high pressure hose, either 3/4", 5/8" or 3/2" as standard, or 1/2" as option. Stainless steel commercial quality construction casing. Pressure relief valve maintaining safe maximum pressure. Thermal relief valve prevents overheating. Auto mixing chemical feature allows automatic switching from Chemical to rise at the spray valve. Plug and play electrical connectors for easy upgrade and sensing options. De-liming assembly. Full service and warranty support. Proven tried and tested designs for commercial applications. Soap and sanitizer pump options for efficient chemical mileage. Hot water capability up to 71°C (160°F) max temperature. These pressure options: 500, 800 and 1000 PSI.	New	Wall Mount				No	No	No	No	No	No	No	No	No	No	No	No	No	No	13	13	No	No	No	No	No	No	No	No	No	Fisher	296S1	T&S Brass			
CDH OS-TL-05 ID 10	A	Pot Washing Room	1	05.10.03	Pot washer	Pot/Pan/Utensil Washer, front loading with split door design, (10) pan capacity, over/under rotating arms, 2/48 minute adjustable timer, up to 20 racks/hour, includes 1" (flat grid) (1) tray rack & (1) flat bottom rack, pre-rinse spray hose, sanitizing with 70° booster line, vent fan control, stainless steel construction, 480x600x90, cULus, BSSC Certified, NSF, ENERGY STAR®. Standard warranty - 1 year limited warranty. Drain water tempering kit. Combination rack. Powered Vent Fan Kit. Water hammer arrestor kit, includes 3/4" brass pressure regulator valve. 3/4" brass pressure regulator.	New	Floor				1270	762	2032	2083	3	70	No	Direct	No	No	No	No	No	19mm	19mm	No	No	50mm Drain to Grease trap	No	No	No	No	No	Steel construction.	Hobart	PW-20	Champion				
CDH OS-TL-05 ID 10	ME	Pot Washing Room	1	05.10.04	Condensate hood	The kitchen hood shall be constructed from 18 gauge stainless steel. The kitchen hoods shall be supplied complete with color casing / main body, inner liner, exhaust duct, baffle plates, condensate channel, drain tap and assembly brackets. Outer casing panels shall be constructed of stainless steel with a brushed satin finish. Each joint shall be welded and liquid tight, avoiding harmful dripping of condensate. All exposed welds are ground and polished to the original finish of metal. Condensation is achieved by the use of angled internal baffles and deflectors. Efficient exhaust is maintained by using linear static coils combined with the large internal volume. Hood complete with surface mount vapor proof light fixture(s). The lighting shall be suitable for single-phase power supply and shall be UL listed incandescent type, suitable for condensate hoods. Condensate channels/gathering shall form part of the main construction of the canopy and run the entire perimeter of the hood. The drain tap shall be manufactured from stainless steel.	New	Ceiling					1524	1219	609	No	No	No	No	No	No	No	No	No	No	No	No	No	25.4mm indirect Drain	Yes	No	No	No	No	Steel construction.	Halton		Gaylord				
CDH OS-TL-05 ID 10	A	Pot Washing Room	1	05.10.05	Stainless steel clean pot wash table (5 feet in length)	Stainless steel construction, type 304, #4 finish. Length to suit design x 760mm wide x 864mm high, stainless steel top with 2.0mm stainless steel or galvanized steel sub-top. Hot channel reinforcement to be stainless steel or galvanized steel on centre. Legs to be stainless steel, tubing or square welded to subtop. Stainless steel cross bracing as required. Sound deadening as required. Backsplash to include radius corner, applied to wall where required. Bullet feet for tables without m/s services, flanged feet secured to floor with a.s. fasteners for tables with m/s services.	New	Floor			Variable	762	864	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	Steel construction.	Custom Fabricated	Custom Fabricated						
CDH OS-TL-05 ID 10	ME	Pot Washing Room	1	05.10.06	Stainless steel overshelf	Stainless steel construction, type 304, #4 finish. Length to suit design x 300mm wide x 150mm high, stainless steel top with stainless steel or galvanized steel sub-top. Hot channel reinforcement to be stainless steel or galvanized steel on centre.	New	Wall			To align with worktable underneath	304.8		No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	Steel construction.	Custom Fabricated	Custom Fabricated						
CDH OS-TL-05 ID 10	A	Pot Washing Room	1	05.10.07	Stainless steel trench drain	Stainless steel construction, type 304, #4 finish. Length and width to suit design x 150mm deep. All radius corners, 1.5mm stainless steel pan Honeycomb or other patterned grating, removable in sections. Provide strainer at all drains. Positioned at wetlines and fit fry pan. Quantity and size to be confirmed based on final design.	New	Floor			See Long Description	See Long Description	See Long Description	No	No	No	No	No	No	No	No	No	No	No	No	No	2 @ 3" direct to grease trap	No	No	No	No	No	No	Steel construction.	Custom Fabricated	Custom Fabricated						
CDH OS-TL-05 ID 10	A	Pot Washing Room	3	05.10.08	Pot rack	Mobile Pot & Pan Rack, 48"W x 24"D x 68"H, (4) shelves acid embossed stainless steel (2) polyurethane swivel casters & (2) polyurethane swivel casters with brake, NSF.	New	Floor			Variable	609	1727	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	Plastic Construction.	Metro	PR48ES	Cambro					
CDH OS-TL-05 ID 10	A	Pot Washing Room	2	05.10.09	Waste bin with duty	Container, round, open type, 20-gallon capacity, high-impact plastic construction, grey. Lid, round, for 20 gallon container, blue. Duty container, black.	New	Mobile						No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	Plastic Construction.	Rubbermaid	Brute 2620						
CDH OS-TL-05 ID 10	ME	Pot Washing Room	1	05.10.10	Stainless steel hand sink	Hand Sink, pedestal mounted base, 13-1/2" wide x 9-3/4" front-to-back x 6-3/4" deep bowl, 304 stainless steel construction, splash mount gooseneck spout, pedal valve, P-trap, tall plate, basket drain, deep-drain seamless design-positive drain, inverted "Y" edge, NSF. Antimicrobial finish on bowl only. Emergency Eye Wash Unit, faucet-mount, fits in place of aerator on spout, (2) dust covers, pull valve activates fountain, polished chrome finish. Anti-Scald Valve, for emergency eye wash, 1/2" NPT, 65-95°F (meets ANSI Z358.1 & ASSE 1017 standards). Left & right side splashplates.	New	Wall	14.5	14.5	376	480	1019	No	No	No	No	No	No	No	No	No	No	No	13	13	No	38	Yes	No	No	No	No	No	Hands free operation with eye wash.	Eagle	HSA-10-FA-P	Advance Tabco		Custom Fabricated		
CDH OS-TL-05 ID 11	A	Best Chilling	1	05.11.01	Best Chiller	Modular Best Chiller, Rock-In, remote refrigeration, accepts (1) 26" W x 32" D x 73.5" H trolley, 200 lbs. from 165°F to 38°F chill capacity/90 minutes, 230 lbs. from 165°F to 38°F chill capacity/120 minutes, 7" LCD touch screen control with Quick Start & A.I. Care functionality, insulated panels, cabinet assembly, automatic or manual operation, programmable, (1) core temp probe included, stainless steel interior & exterior, UL, 1 year parts & labor warranty standard. 208V/60/1-ph, 8.2 amps, standard. Air-cooled remote condensing unit, 208V/60/3-ph, Four year compressor warranty. 2" insulated fire panel. Coarse generator. Probe holder (for liquids).	New	Floor				1320	1066	2336	2083	50	60	1	Direct	No	Yes	Yes	Yes	No	No	No	No	No	25	No	No	No	No	No	Steel construction.	American Panel Corporation	AP208C-1T	Defield				
CDH OS-TL-05 ID 11	A	Best Chilling	2	05.11.02	Mobile Chiller Rack	Mobile racks available, 26" W x 32" D x 73.5" H	New	Mobile						No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	Steel construction.	Custom Fabricated	Custom Fabricated							
CDH OS-TL-05 ID 12	ME	Prepared Food Holding	1	05.12.01	Pre-fabricated insulated wall and ceiling panels and- refrigeration-system	ULC listed pre-fabricated insulated wall and ceiling panels, 4" (100mm) thick with polyurethane insulation. Panels to have a tongue and groove configuration and fastened together with a mechanical cam-lock fastener. Finish to be stainless steel. Rooms complete with 1220mm sliding doors complete with cross double acting insulated doors complete with viewing. All rooms complete with LED light fixtures to provide 50 foot candle lighting levels. Stainless steel hand plates on all exposed exterior.	New	Floor	Custom	Custom	Custom	Custom	Custom	Custom	1201	15	60	No	Direct	No	Yes	Yes	No	No	No	No	No	No	No	No	No	No	No	Custom Fabricated Panel Construction	Norbec	Custom	Canadian Curtis	Masterbuilt				
CDH OS-TL-05 ID 12	ME	Prepared Food Holding	1	05.12.02	Refrigeration evaporator coil	Coil and balanced in match the compressor and must be capable of maintaining internal room temperature (max. +3C for coolers, min. -18C for freezers) while considering humidity levels of surrounding areas, product type and load, heat infiltration and temperature of incoming product. Corrosion free assembly. Time initiated air defrost cycles for coolers. Electric hot gas defrost for freezers.	New	Floor	Custom	Custom	Custom	Custom	Custom	1201	15	60	No	Direct	No	Yes	Yes	No	No	No	No	Yes	No	No	No	No	No	No	No	Custom Fabricated.	Norbec	Custom	Canadian Curtis	Masterbuilt				
CDH OS-TL-05 ID 12	ME	Prepared Food Holding	1	05.12.03	Refrigeration condensing unit	Remote Water Cooled Sool Condensing unit sized to suit walk-in room size. Unit to include mounting on top of the room. Rack design refrigeration system would be considered if it can be accommodated within the design.	New	Floor	Custom	Custom	Custom	Custom	Custom	2083	20	60	No	Direct	No	Yes	No	Yes	No	No	No	No	No	No	No	No	No	No	No	Custom Fabricated.	Norbec	Custom	Canadian Curtis	Masterbuilt				
CDH OS-TL-05 ID 12	ME	Prepared Food Holding	1	05.12.04	Temperature Alarm	Hi-low temperature alarm, recessed in wall panels, with dry contacts for remote monitoring, rechargeable battery having operating range of -50C to +50C. Cavity temperature bulbs to be positioned behind evaporator coil (no visible wires). Interconnected to building automation system and remote monitoring and logging system.	New	Floor	Custom	Custom	Custom	Custom	Custom	1201	15	60	No	Direct	No	Yes	Yes	No	Yes	No	No	No	No	No	No	No	No	No	No	Custom Fabricated.	Norbec	Custom	Canadian Curtis	Masterbuilt				
CDH OS-TL-05 ID 12	A	Prepared Food Holding	2	05.12.05	Shelving unit	Constructed of steel with removable polypropylene overlays or polyester, thermoplastic/polypropylene construction. Construction to be corrosion resistant and coated with an microbial substance. Minimum dimensions to be 610mm wide. All units to include cart washable casters, two locking. Minimum four sets of shelves. Shelves to be adjustable. Overall dimension of unit to vary depending on the layout of the room. Typically 1200mm or 1500mm wide.	New	Mobile	5	5	610				1752	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	Plastic Construction.	Metro	Max Q	Cambro					
CDH OS-TL-05 ID 12	A	Prepared Food Holding	4	05.12.06	Angle racks	Tray Rack, mobile, end load, single section, pass-thru, 20"W x 63-1/4"H, 23"D, pass-thru, closed sides, with slides for (18) 15" x 20" or (18) 16" x 22" trays, slides on 3" casters, lined aluminum construction, NSF. Continuous Bumper, gran. Mobile Tray Rack Top stop.	New	Mobile	10	10	510	510	1606	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	Steel construction.	Metro	RD15N	Hatch		Custom Fabricated		
CDH OS-TL-05 ID 13	ME	Meal Assembly	1	05.13.01	Exhaust hood with fire protection system	The hood shall be designed with Side-Jet technology to reduce the exhaust airflow rate required, and to improve the capture and containment efficiency of the hood, while reducing energy consumption. The Side-Jet technology shall be retrofitted through a special discharge panel and shall not exceed 10% of the calculated exhaust airflow. The Side-Jet technology discharge velocity will be a minimum of 1500 feet per minute. Slot or grille type discharge shall not be used. The Side-Jet technology shall be internally mounted with a speed control and will not require a fire damper or electronic shut down in fire mode. The integral front discharge make up air plenum shall be manufactured of the same material as the hood. The box of the plenum will be perforated stainless steel to deliver low velocity air to the space and to minimize room turbulence while withdrawing the occupied zone. The SFP fire suppression system is an industry leader in rugged components and superior fire suppression. The versatile SFP system incorporates a stored pressure cylinder and delivers a wet chemical agent to a fire, quickly suppressing and containing fires in a wide variety of applications.	New	Ceiling				See Long Description	See Long Description	See Long Description	2 @ 120V1	20	60	No	Direct	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	CFM T.B.C. Type I Hood	Halton	KVE	Spring Air		Gaylord	
CDH OS-TL-05 ID 13	A	Meal Assembly	1	05.13.02	Combination steam connection oven, electric - 10 GN capacity	Combi Oven/Steamer, electric, (10) 18" x 26" full size sheet or (20) 12" x 20" full size hotel pan capacity. Control with 7 modes, Combi-Steamer with 3 modes, core temp probe with 6 point measurement, hand shower with automatic retracting system, mobile oven rack included, (10) grid shelves, ethernet interface, 208V/60/3-ph, 103 amps, 94.5 kW, 2 years parts and labor, 3 years steam generator warranty. Manufacturer Technical Start-Up electric units, by an authorized Service Company. Water Filtration Double Cartridge System, for Combi-Duo if used for more than 2 units includes: (1) double heat with pressure gauge, (2) filter & (1) filter installation kit for each additional unit and (1) additional heat & additional cartridge. Maximum (6) cartridges. The carbon block technology reduces the effects of sediment, chloramines and chlorine while providing the required flow rates. Heat Shield, for left side panel. Unit Connection Kit, includes: water connection hose 1/2" (2 m) with 3/4" union & 1/2" 50mm (2") and drain side 1/4" HT low 6" 2" HT low 45" 1/4 HT low 45" 1/4 HT low 500mm, 1 x sleeve. Externally attached core temperature probe. Control panel protection. Mobile with casters (4) with locks.	New	Floor								1067	1037	1037	103	60	No	Direct	No	No	No	No	13	No	13	No	52	No	No	No	No	No	Steel construction.	Rational	SCC 102 E	Conotherm		Blodgett
CDH OS-TL-05 ID 13	A	Meal Assembly	1	05.13.03	Rapid cook oven with stand	Commercial grade rapid cook oven complete with type 304 stainless steel interior and removable grease pan, integral incrusting catalytic converter for UL7108 listed ventless operation, independently controlled dual rotors, external air filtration, and smart menu system, to include stainless steel equipment stand.	New	Counter				762	660	812	208/240	3	30	No	Yes	No	Yes	No	No	No	No	No	No	No	No	No	No	No	No	No	Steel construction.	Merry Chef	E4	Turbochef		ACP		
CDH OS-TL-05 ID 13	A	Meal Assembly																																								

**Appendix 2K-1 Food Service Equipment List**  
**Updated January 24, 2022**

ID	Category	Department Room Reference	Total Qty	Item Ref No	Item Description	Long Description	Item Status	Mounting	Max Weight (kg)	Ship Weight (kg)	Width (mm)	Depth (mm)	Height (mm)	Volts	Amps	Hz	Watts	Plug Type	BTU/hr	Dedicated Circuit	Tech Connection (data)	Emergency Power	Water - Cold	Water - Hot	Water - Treated	Steam	Drain	Vent	Gas	Vacuum Dental	Vacuum Med	Compressed Air	Item Notes	Sample Manufacturer 1	Sample Model 1	Sample Manufacturer 2	Sample Manufacturer 3				
CDH-OS-TL-05 ID 13	A	Meal Assembly	3	05.13.05	Coffee maker w/ hot water faucet	20900.0011 Duall Coffee Brewer. Portable, mechanical thermostat, brews 18.9 gallons per hour capacity, stainless steel funnel, 3 batch-size settings, electronic timer & grinder interface, upper hot water faucet, variable water bypass, includes (2) GPRs (20900.0004), (2) backwashable legs, 1200A/60/30/50/800 wets, 28 amps, UL NSF, 20950.0004 1.5GPR-FF Coffee Server, 1.5 gallon, top handles, fast flow faucet, stainless decoar, NSF, 12023.0010 RWS1 Stainless Brewer Warmer, 4" adjustable plastic top (for use with GPR and 1.5GPR servers), 120401.01, 100W, 1 amp, cord attached, UL NSF, 20138.1000 Paper Filter, 1.5-3/4" x 5-1/4", white, (for Tea & Coffee-1-1/2 gallons) (500 each per case, price based on 1-229 lbs total weight - call for price on greater quantities), 39000.0005 ECHP-25 Easy Clean High Water System, 25,000 gallon, reduced sediment, chrome tank color, reduction @ 2.1 gm, equipment protection, 0.2 micron, includes a head assembly, integral mounting bracket and cartridge filter, Quick Connect, NSF, 20123.0103 Drip Tray Kit, stainless decoar, for use with RW151	New	Counter					1202298601	30	60	No	Direct	No	No	No	No	No	No	No	No	No	6	No	No	No	No	No	No	No	No	No	Steel Construction	Burn	20900.0011	Falco	Curlis
CDH-OS-TL-05 ID 13	A	Meal Assembly	6	05.13.06	Lowerator (cups)	Stainless steel, Type 304 helarc and spot-welded construction. Removable top, all seams fully welded & polished. Double wall insulated construction. Accommodates various round drop-in tube dispensers. Dispensers are equipped with non-rusting springs that are heat treated for strength & durability. Push handle on one end of unit goes wrap-around bumper. Clean out door in bottom.	New	Mobile						No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	Steel Construction	Burldge	BTRC-M-2020-P					
CDH-OS-TL-05 ID 13	A	Meal Assembly	3	05.13.07	Mobile Coffee Table	Mobile stand to be stainless steel construction, type 304, #4 finish, length to suit design x 760mm wide x 840mm high, stainless steel top with stainless steel or galvanized steel sub-top. Hat channel reinforcement to be stainless steel or galvanized steel on one side, legs to be stainless steel, tubing or square welded to sub-top. Stainless steel cross bracing as required. Sound deadening as required. 4 all swivel non-marking rubber cart-washable casters with brakes.	New	Mobile			Variable	762	864	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	Steel construction	Custom Fabricated	Custom Fabricated						
CDH-OS-TL-05 ID 13	A	Meal Assembly	3	05.13.08	Tray Assembly Table - Mobile	Stainless steel type 304 with Camco strips installed with screws through solid top, start and finished end capped in stainless steel, 4 length underside 0.14" from floor, no lip, 4 inch heavy duty swivel casters with side brakes	New	Mobile			3353	502	889	1201	15	60	No	Yes	No	No	No	No	No	No	No	No	No	No	No	No	No	No	Steel construction	Hatch	PTS-M-1[1]	Burldge B2-ST-M-2360					
CDH-OS-TL-05 ID 13	A	Meal Assembly	6	05.13.09	Gravidy Shelving	Stainless steel type 304 with helarc and spot welded construction. Open style, solid base with 4 independent moving 26"20" shelves. Shelf front can be labeled. Each shelf can be used in horizontal position raised at the back by 5" from horizontal or raised at back by 6.5" from horizontal position. Front of shelf to remain stationary. Security stopper at 0 deg for each shelf. Spacing between shelf surfaces to be 8" in horizontal position. Each shelf to hold up to 20lbs of product and to extend 3" past the bumper. First shelf to be mounted at 37.75" from the floor. Blue wrap around bumpers with internal stainless steel core. Push handle on rear with blue grip. 48" wheel non-marking casters with side brakes.	New	Mobile				762	660	1778	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	Steel construction	Burldge	B2-FSCS-M-2620-4	Hatch			
CDH-OS-TL-05 ID 13	A	Meal Assembly	2	05.13.10	Hot food tables (5 well)	Hot Food Table, Electric, 74" L, (5) 12" x 20" hot food wells with drains, infinite control, 6" poly cutting board, open base, stainless steel plate shelf top, sides, bottom shelf with 3" rear rear casters, NSF, UL, cUL, Fill handle. Composite cutting board, 12" x 16" deep polyethylene board. Chief side stainless steel top 14"	New	Mobile			1828	762	864	2083	20	60	No	No	No	No	No	No	Yes	No	No	No	No	No	No	No	No	No	No	Steel construction	Deflect	EHE74C	Hatch				
CDH-OS-TL-05 ID 13	A	Meal Assembly	1	05.13.11	Cold food tables (5 well)	Cold Food Serving Counter, stainless steel, 5 well, insulated with refrigerated base, hinged doors on base. Self-contained refrigeration. Push/pull handles, stainless steel.	New	Mobile			800	1975	927	1201	8	60	No	Plug	No	No	Yes	No	No	No	No	No	No	No	No	No	No	No	Steel construction	Hatch	CFS-M-5-OS-RDWS-RB	Deflect SCS-74-SP					
CDH-OS-TL-05 ID 13	A	Meal Assembly	3	05.13.12	Ticket Printers	Adjustable round table dish dispenser to be fabricated from stainless steel, self-leveling, self-adjustable and to be adjustable chrome diameter. Approximately 5 1/8" dia. plate per table. To be constructed as follows: stainless steel, type 304, helarc and spot-welded construction, removable top, all seams fully welded & polished, double wall insulated construction, accommodates various diameter ranges of round drop-in tube dispensers. Dispensers are equipped with non-rusting springs that are heat treated for strength & durability, push handle on one end of unit, wrap-around bumper with internal stainless steel core for strength and durability, clean out door in bottom, 4" x 5" swivel, non-marking casters with 4 side brakes, variable heat setting thermostat with on/off pilot light indicator, approved power supply cord with 3 prong end cap.	New	Counter						1201	15	60	No	Plug	No	Yes	Yes	No	No	No	No	No	No	No	No	No	No	No	No	No	Steel construction						
CDH-OS-TL-05 ID 13	A	Meal Assembly	3	05.13.13	Heated beverage (entire dish - double tube)	Adjustable round table dish dispenser to be fabricated from stainless steel, self-leveling, self-adjustable and to be adjustable chrome diameter. Approximately 5 1/8" dia. plate per table. To be constructed as follows: stainless steel, type 304, helarc and spot-welded construction, removable top, all seams fully welded & polished, double wall insulated construction, accommodates various diameter ranges of round drop-in tube dispensers. Dispensers are equipped with non-rusting springs that are heat treated for strength & durability, push handle on one end of unit, wrap-around bumper with internal stainless steel core for strength and durability, clean out door in bottom, 4" x 5" swivel, non-marking casters with 4 side brakes, variable heat setting thermostat with on/off pilot light indicator, approved power supply cord with 3 prong end cap.	New	Mobile						1201	6	60	No	Plug	No	Yes	No	No	No	No	No	No	No	No	No	No	No	No	No	No	Steel construction	Hatch	1ADTH-M-1720"	Deflect			
CDH-OS-TL-05 ID 13	A	Meal Assembly	3	05.13.14	Entire dish cart (mini)	Stainless steel, Type 304 helarc and spot-welded construction. Stainless steel tubular frame assembly. Wire design Ergonomic raised working height of 23 1/2" (597mm) to eliminate bending. Tilted dish compartment with reinforced solid stainless steel base. Dividers adjustable at 1" centres (dividers are optional). Front gate is completely removable and slides under unit when not in use. Dwell bumpers.	New	Mobile						No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	Steel construction	Hatch	UDCW-D-3610	Burldge				
CDH-OS-TL-05 ID 13	A	Meal Assembly	3	05.13.15	Air curtain refrigerator	Stainless steel doors and hinges with glass and door locks. Touch screen electronic control panel. Standby mode activated after 30 sec of inactivity. Energy saving mode - automatically activates after 4 hrs of door opening inactivity. Manager lockout feature. Demand defrost detection. Supercool mode for product when required. All stainless steel construction inside and out with complete with foamed in place polyurethane insulation. Lifetime energy saving breaker caps. B-134 refrigeration. Plastic coated evaporator fin coils. Non-electric evap pan. One piece snap in magnetic door gaskets. Stainless steel pan slides x 15 sets. Flush recessed side hand grips, cord and plug.	New	Mobile				120	20	60	No	Plug	No	Yes	No	Yes	No	No	No	No	No	No	No	No	No	No	No	No	No	No	Steel construction	Burldge	B-COOL	Hatch			
CDH-OS-TL-05 ID 13	A	Meal Assembly	12	05.13.16	Dish cart (side dishes, kils, bowls, plates, domes)	Stainless steel, Type 304 helarc and spot-welded construction. Stainless steel tubular frame assembly. Wire design Ergonomic raised working height of 23 1/2" (597mm) to eliminate bending. Tilted dish compartment with reinforced solid stainless steel base. Dividers adjustable at 1" centres (dividers are optional). Front gate is completely removable and slides under unit when not in use. Dwell bumpers.	New	Mobile						No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	Steel construction	Hatch	UDCW-D-3610	Burldge				
CDH-OS-TL-05 ID 13	A	Meal Assembly	3	05.13.17	Waste bin with duty	Container, round, open type, 20-gallon capacity, high-impact plastic construction, grey, Lid, round, 20 gallon container, blue. Duty containers, black.	New	Mobile						No	No	No	No	No	No	No	Yes	No	No	No	No	No	No	No	No	No	No	No	Plastic Construction	Rubbermaid	Brute 2620						
CDH-OS-TL-05 ID 13	ME	Meal Assembly	2	05.13.18	Stainless steel hand sink	Hand Sink, pedestal mounted base, 13-1/2" wide x 9-3/4" front-to-back x 6-3/4" deep bowl, 304 stainless steel construction, splash mount gooseneck spout, pedal valves, P-trap, tail piece, basket drain, deep-drain seamless design-positive drain, inverted "Y" edge, NSF, Antimicrobial finish on bowl only. Emergency Eye Wash Unit, faucet-mount, fits in place of aerator on spout, (2) dust covers, pull valve activates fountain, polished chrome finish. Anti-Scald Valve, for emergency eye wash, 1/2" NPT, 65°-95°F (meets ANSI Z358.1 & ASSE 1017 standards). Left & right side splashes.	New	Wall	14.5	14.5	376	480	1019	No	No	No	No	No	No	No	No	No	No	No	No	13	13	No	No	38	Yes	No	No	No	No	Hands free operation with eye wash.	Eagle	HSA-10-FA-P	Advance Tabco	Custom Fabricated	
CDH-OS-TL-05 ID 13	A	Meal Assembly	1	05.13.19	Roll in refrigerator	Refrigerator, in-line refrigeration, (2) glass doors with locks, cam-tilt hinges, digital temperature control, incandescent interior lighting, stainless steel ramps, stainless steel front & sides, aluminum interior, 1/2 HP, 115/60/1-1, 11.8 amps, NEMA 5-15P, (accommodates 27"W x 29"D x 66"H carts), cULus, Stainless steel back.	New	Floor					120	12	60	No	Plug	No	No	Yes	No	No	No	No	No	No	No	No	No	No	No	No	Steel construction	True Manufacturing	STR2RR-2G	Traulsen	Randell				
CDH-OS-TL-05 ID 13	A	Meal Assembly	2	05.13.20	Angle rack for roll in refrigerator	Tray Rack, mobile, end load, single section, pass-thru, 20"W x 63-1/4"H, 23"D, pass-thru, closed sides, with slides for (18) 15" x 20" or (18) 16" x 22" trays, slides on 3" casters, nested aluminum construction, NSF. Continuous bumper, ggs. Mobile Tray Rack stop.	New	Mobile			609	660	1625	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	Steel construction	Metro	RD15N	Hatch					
CDH-OS-TL-05 ID 13	A	Meal Assembly	1	05.13.21	Ice machine	Ice Maker, Cube-Style, 30"W, air-cooled, self-contained condenser, production capacity up to 1275 6/24 hours at 70°/50° (1089 BARS certified @ 60°/70°), stainless steel finish, crescent cube style, R-404A refrigerant, 208/230/60/3-1, 13.2 amps, NSF, UL, Warranty 5-year parts on compressor & air-cooled condenser. Warranty 5-year parts & labor on evaporator. Warranty 3-year parts & labor on entire machine. Transformer Kit - 4 wire to 3 wire (eliminates need for dedicated neutral). Ice Bin, 52"W, top-hinged front-opening door, 900-lb ice storage capacity, for top-mounted to makers, stainless steel exterior, painted top included, Antimicrobial Agent, ETL, ETL-Listed, Sanitation, Top Kit, 22", ABS.	New	Mobile					762	695	1054	2081	13.2	60	No	Direct	No	Yes	No	No	No	No	10mm		No	No	No	No	No	No	No	Steel Construction	Hoshizaki	KM-1340MAJ, B-900	Scottman	Manitowoc	
CDH-OS-TL-05 ID 14	A	Cart Marshalling Room (Internal)	10	05.14.01	Tray delivery cart (24 tray capacity with on board refrigerator and heating)	Carts to be hot-line tray delivery system, complete with on-board heating and cooling, active temperature maintenance and boost cycle for hot food. The cart is to handle high capacity, hot line tray preparation and the transportation of hot and cold meals, the cart incorporates leading technology and maneuverability, ensuring it is both easy to learn and operate. The unit combines efficiency, style and durability, while featuring an ergonomic design that promotes safety in all aspects of its function. The cart is to consist of the following: stainless steel interior and chassis, aluminum framed doors with ABS exterior and fiberglass interior laminated door panels, anti-static high impact thermoplastic top and side panel, high density rigid insulation throughout and wrap-around bumper. The cart is to have a handle, hand grip, top handle, 2 vertical handles, optional horizontal handle add-on, easy to maneuver, low noise emission, optional flat top, optional central brake. The cart is to have the convenient sanitation features: hose washable rating, removable vent panels (no tools required), disassemble parts with no tools, frame gaskets easily removed and replaced by hand, and microbial door latch mounted to frame, rounded sanitary internal corners. This cart to accommodate 24 trays.	New	Mobile					2083	40	60	No	Plug	No	Yes	Yes	Yes	Yes	Yes	No	No	No	No	No	No	No	No	No	No	No	No	Allow for electrical services within On Floor Food Service (Galleys) as these units can be plugged in during meal service.	Burldge	RTS-HL	Hatch		
CDH-OS-TL-05 ID 14	A	Cart Marshalling Room (Internal)	10	05.14.02	Tray delivery cart (12 tray capacity with on board refrigerator and heating)	Carts to be temperature maintenance tray system, that is to be used for room service, the cart is an heated and refrigerated food cart developed to maintain hot and cold food temperatures. The design of the unique single tray system enables the delivery of plated meals on a one piece flat tray. Manufacture standard construction. Control operating system. Stainless steel construction. Stainless steel top with built in plastic bumpers. Removable handle and perimeter barrier. Heavy duty bumper with wrap around hard resin bumper. Four heavy duty cable bearing non-marking casters, 2 x 200mm (8") fixed and 2 150mm (4.5") swivel bumpers. Push/pull and protected cable storage. Cart to accommodate 12 trays.	New	Mobile						2083	25	60	No	Plug	No	Yes	Yes	Yes	Yes	No	No	No	No	No	No	No	No	No	No	No	Allow for electrical services within On Floor Food Service (Galleys) as these units can be plugged in during meal service.	Burldge	Logix Uno BLKXO.LUNO.12 Optima RG	Hatch			
CDH-OS-TL-05 ID 14	ME	Cart Marshalling Room (Internal)	1	05.14.03	Stainless steel hand sink	Hand Sink, pedestal mounted base, 13-1/2" wide x 9-3/4" front-to-back x 6-3/4" deep bowl, 304 stainless steel construction, splash mount gooseneck spout, pedal valves, P-trap, tail piece, basket drain, deep-drain seamless design-positive drain, inverted "Y" edge, NSF, Antimicrobial finish on bowl only. Emergency Eye Wash Unit, faucet-mount, fits in place of aerator on spout, (2) dust covers, pull valve activates fountain, polished chrome finish. Anti-Scald Valve, for emergency eye wash, 1/2" NPT, 65°-95°F (meets ANSI Z358.1 & ASSE 1017 standards). Left & right side splashes.	New	Wall	14.5	14.5	376	480	1019	No	No	No	No	No	No	No	No	No	No	13	13	No	No	38	Yes	No	No	No	No	Hands free operation with eye wash.	Eagle	HSA-10-FA-P	Advance Tabco	Custom Fabricated			
CDH-OS-TL-05 ID 15	A	Cart Marshalling Room (External)	3	05.15.01	Bulk Transport Carts - Hot (Residential Care)	Transport and storage cart with hot food compartments, adjustable temperatures, digital temperature display, fully welded stainless steel interior, wrap around caster at base, doors that open to an angle of 270 degrees, non protruding hinges, foamed in place insulation to minimize wall thickness, door handles with locking functions, door with gaskets, casters - 2 with brakes and 2 fixed.	New	Mobile			57	525	810	1201	15	60	No	Yes	No	No	No	Yes	No	No	No	No	No	No	No	No	No	No	No	Burldge	Thermobox F120	Cambro					
CDH-OS-TL-05 ID 15	A	Cart Marshalling Room (External)	3	05.15.02	Bulk Transport Carts - Cold (Residential Care)	Transport and storage cart with cold food compartments, adjustable temperatures, digital temperature display, fully welded stainless steel interior, wrap around caster at base, doors that open to an angle of 270 degrees, non protruding hinges, foamed in place insulation to minimize wall thickness, door handles with locking functions, door with gaskets, casters - 2 with brakes and 2 fixed.	New	Mobile			85	525	750	1201	15	60	No	Yes	No	No	No	Yes	No	No	No	No	No	No	No	No	No	No	No	Burldge	Thermobox K120	Cambro					
CDH-OS-TL-05 ID 15	A	Cart Marshalling Room (External)	4	05.15.03	Bulk Transport Carts - Hot (Residential Care)	Transport and storage cart with hot food compartments, adjustable temperatures, digital temperature display, fully welded stainless steel interior, wrap around caster at base, doors that open to an angle of 270 degrees, non protruding hinges, foamed in place insulation to minimize wall thickness, door handles with locking functions, door with gaskets, casters - 2 with brakes and 2 fixed.	New	Mobile			57	525	810	1055	1201	15	60	No	Yes	No	No	No	Yes	No	No	No	No	No	No	No	No	No	No	Burldge	Thermobox F90	Cambro					
CDH-OS-TL-05 ID 15	A	Cart Marshalling Room (External)	4	05.15.04	Bulk Transport Carts - Cold (Residential Care)	Transport and storage cart with cold food compartments, adjustable temperatures, digital temperature display, fully welded stainless steel interior, wrap around caster at base, doors that open to an angle of 270 degrees, non protruding hinges, foamed in place insulation to minimize wall thickness, door handles with locking functions, door with gaskets, casters - 2 with brakes and 2 fixed.	New	Mobile			80	525	750	1115	1201	15	60	No	Yes	No	No	No	Yes	No	No	No	No	No	No	No	No	No	No	Burldge	Thermobox K90	Cambro					
CDH-OS-TL-05 ID 16	ME	Housekeeping Room	1	05.16.01	Jarbor sink	Jarbor Sink, 27" x 15" x 17" deep, jarbor sink with drain, overhead shelf, rear-mounted mop holder with (2) locking casters, service faucet with vacuum breaker and 120" hose, 18300 stainless steel	New	Floor			508	711	406	No	No	No	No	No	No	No	No	No	13	13	No	No	50	No	No	No	No	No	Eagle Group	F1916	Fisher	T&S Brass					
CDH-OS-TL-05 ID 16	A	Housekeeping Room	1	05.16.02	Chemical storage shelf	Refer to Appendix 11 Equipment List	New	Floor						No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No									
CDH-OS-TL-05 ID 16	ME	Housekeeping Room	1	05.16.03	Wall mounted sink	Hand Sink, pedestal mounted base, 13-1/2" wide x 9-3/4" front-to-back x 6-3/4" deep bowl, 304 stainless steel construction, splash mount gooseneck spout, pedal valves, P-trap, tail piece, basket drain, deep-drain seamless design-positive drain, inverted "Y" edge, NSF, Antimicrobial finish on bowl only. Emergency Eye Wash Unit, faucet-mount, fits in place of aerator on spout, (2) dust covers, pull valve activates fountain, polished chrome finish. Anti-Scald Valve, for emergency eye wash, 1/2" NPT, 65°-95°F (meets ANSI Z358.1 & ASSE 1017 standards). Left & right side splashes.	New	Wall	14.5	14.5	376	480	1019	No	No	No	No	No	No	No	No	No	No	13	13	No	No	38	Yes	No	No	No	No	Hands free operation with eye wash.	Eagle	HSA-10-FA-P	Advance Tabco	Custom Fabricated			
CDH-OS-TL-05 ID 16	A	Housekeeping Room	1	05.16.04	Housekeeping cart	Refer to Appendix 11 Equipment List	New	Mobile						No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No									
CDH-OS-TL-05 ID 17	ME	Soiled Cart Receiving/Sorting Room	1	05.17.01	Hand sink	Hand Sink, pedestal mounted base, 13-1/2" wide x 9-3/4" front-to-back x 6-3/4																																			





Appendix 2K-1 Food Service Equipment List  
Updated January 24, 2022

ID	Category	Department Room Reference	Total Qty	Item Ref No	Item Description	Long Description	Item Status	Mounting	Max Weight (kg)	Ship Weight (kg)	Width (mm)	Depth (mm)	Height (mm)	Volts	Amps	Hz	Watts	Plug Type	BTU/hr	Dedicated Circuit	Tech Connection (data)	Emergency Power	Water - Cold	Water - Hot	Water - Treated	Steam	Drain	Vent	Gas	Vacuum Dental	Vacuum Med	Compressed Air	Item Notes	Sample Manufacturer 1	Sample Model 1	Sample Manufacturer 2	Sample Manufacturer 3		
CDH-IP-01 ID 75	A	On Floor Food Service / Gallery (MedSurg)	4	0175.04	Coffee Brewer and Warmers complete with hot water dispenser	Coffee Brewer, Portable, mechanical thermostat, brews 18.9 gallons per hour capacity, stainless steel funnel, 3 batch-size settings, electronic timer & grinder interface, upper hot water faucet, variable water bypass, includes (2) service, 4" back adjustable legs, 1200/600"ph, 5950 watts, 29 amps, UL, NSF, 1.5 GPR/F Coffee Server, 1.5 gallon, top handles, fast flow faucet, stainless decor, NSF, Satellite Brewer/Warmer, 4" adjustable plastic legs (for use with 1 GPR and 1.5 GPR servers), 120/600"ph, 100w, 1 amps, cord attached, UL, NSF Paper Filters, 13.3x1.14" white, (for Tea & Coffee) 1-1/2 gallon, High Water System, 25,000 gallon, reduced sediment, chlorine taste & odor, reduction @ 2.1 gpm, equipment protection, 0.2 micron, includes a head assembly, integral mounting bracket and cartridge filter, Quick Connect, NSF, Drip Tray Kit, stainless floor.	New	Counter				1200/2860	1	30	60	No	No	No	No	Direct	No	No	No	No	No	No	6	No	No	No	No	No	No	Steel Construction	Bunn	2060.0011	Felco	Curtis	
CDH-IP-01 ID 75	A	On Floor Food Service / Gallery (MedSurg)	4	0175.05	S.S. Work Table (mobile)	Stainless steel construction, type 304, #4 finish, Length to suit design x 30" wide x 34" high, stainless steel top with stainless steel or galvanized steel sub-top. Hat channel reinforcement to be stainless steel or galvanized steel on centre. Legs to be stainless steel, tubing or square welded to subtop. Stainless steel cross bracing as required. Sound deadening as required. 4 all swivel non-marking rubber cast-washable casters with brakes, S.S. drawers.	New	Mobile			Varies based on layout - typically 1524	762	864	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	Steel construction	Custom Fabricated	Custom Fabricated				
CDH-IP-01 ID 75	ME	On Floor Food Service / Gallery (MedSurg)	4	0175.06	S.S. Work Table with Sink	Stainless steel construction, type 304, #4 finish, Length to suit design x 760mm wide x 864mm high, stainless steel top with 2.0mm stainless steel or galvanized steel sub-top. Hat channel reinforcement to be stainless steel or galvanized steel on centre. Sink to be minimum 18" x 16" x 12" deep complete with hot and cold water faucet with swing spout. Legs to be stainless steel, tubing or square welded to subtop. Stainless steel cross bracing as required. Sound deadening as required. Backsplash to include radius coved corner, sprayed to wall where required. Bulet test for tables without m/e services, flanged feet secured to floor with s.s. fasteners for tables with m/e services, S.S. drawers.	New	Floor				Varies based on layout - typically *1524mm to 1628"	762	864	1201	15	60	No	No	Plug	No	No	No	No	13	13	No	No	38	No	No	No	No	No	Steel construction	Custom Fabricated	Custom Fabricated		
CDH-IP-01 ID 75	A	On Floor Food Service / Gallery (MedSurg)	4	0175.07	Microwave Oven	Commercial Microwave Oven, 0.6 cu. ft. capacity, 1200 watts, heavy volume, 4-stage cooking, (11) power levels, (100) memory settings, 60-minute max cooking time, LED display, touch control, interlock safety switch, ADR compliant touch panel, audible end of cycle signal, side hinged door with tempered glass, sealed ceramic interior shelf, lighted interior, stainless steel exterior & interior, 120/600"ph, 16.8 amps, 20 MCA, 2000 watts (total), NEMA 5-20P, eTLux, ETL Sanitation, 3-year full warranty.	New	Counter						1201	20	60	No	No	Plug	No	No	No	No	No	No	No	No	No	No	No	No	No	No	Steel construction	Amara	HDC1242	Panasonic		
CDH-IP-01 ID 75	ME	On Floor Food Service / Gallery (MedSurg)	4	0175.08	S.S. Wall Mounted Microwave Shaving	2.0mm type 304 stainless steel wall cladding to be wall mounted where impact of moisture resistance is required by design.	New	Wall Mounted			Variable	304.0	Variable	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	Steel construction	Custom Fabricated	Custom Fabricated				
CDH-IP-01 ID 75	ME	On Floor Food Service / Gallery (MedSurg)	4	0175.09	Hand Free Hand Sink	Hand Sink, pedestal mounted base, 15-1/2" wide x 9-3/4" front-to-back x 6-3/4" deep bowl, 304 stainless steel construction, splash mount gooseneck spout, pedestal valves, P-trap, tall pipe, basket drain, drain-train seamless design-positive drain, inverted "Y" edge, NSF, Antimicrobial finish on bowl only. Emergency Eye Wash Unit, faucet-mount, fits in place of aerator on spout, (2) dust covers, full valve activates fountain, polished chrome finish, Anti-Scald Valve, for emergency eye wash, 1/2" NPT, 60°-95°F (meets ANSI Z358.1 & ASSE 1017 standards). Left & right side splashes.	New	Wall	14.5	14.5	376	480	1019	No	No	No	No	No	No	13	13	No	No	No	No	No	No	38	Yes	No	No	No	No	No	Hands free operation with eye wash.	Eagle	HSA-10-FA-P	Advance Tabco	Custom Fabricated
CDH-IP-01 ID 75	A	On Floor Food Service / Gallery (MedSurg)	4	0175.10	Ice / Water Dispenser	Ice / Water Dispenser, Cabinet-Style, air-cooled, self-contained condenser, production capacity up to 262 8oz cups at 77°F (21°) & AHRI certified @ 90°F (32°), 10 lb built-in storage capacity, counter mount push button operation, stainless steel bin & exterior, protected with Antimicrobial Agent, R-404A refrigerant, 4" legs, 115/600"ph, 8.5 amps, NEMA 5-15P (optional stand sold separately), NSF, UL, Warranty: 3-Year parts & labor on entire machine. Warranty: 3-Year parts on compressor, air-cooled condenser. Equipment Stand, for dispenser/dispensers, cabinet base with locking door, stainless steel, corrosion resistant exterior, with flat top, with painted flanged legs, ETL Sanitation. Complete with water filter.	New	Counter							421	613	805	1201	20	No	Plug	No	No	No	No	No	13	No	38	No	No	No	No	Steel construction	Hoshizaki	DCM-270BAH	Scottman	Folet	
CDH-IP-02 ID 64		On Floor Food Service / Gallery (CUHCU)			Tray delivery cart (Noted in the kitchen)		New							2893	40	60	No	Plug	No	Yes	Yes	No	No	No	No	No	No	No	No	No	No	Steel construction	Burbridge	RTS HL					
CDH-IP-02 ID 64	A	On Floor Food Service / Gallery (CUHCU)	1	0264.01	Combi-Oven - Ventless	Future item service to be rough-in and capped for future install	New	Floor						2893	70	60	No	Direct	No	Yes	No	No	13	No	13	No	52	No	No	No	No	No	Steel construction	Rational	SOC WE E3E 600-9-6-E	Conotherm	Budgette		
CDH-IP-02 ID 64	A	On Floor Food Service / Gallery (CUHCU)	1	0264.02	Reach In Dual Temp Double Door Refrigerator / Freezer	Refrigerator/Freezer Dual Temp Cabinet, reach-in, 48" wide, self-contained refrigeration, stainless steel exterior, aluminum interior, standard depth cabinet, (2) lockable full-height doors, (3) adjustable wire shelves per section, interior LED lighting, microprocessor controls, 1/5 HP & 1/3 HP, cULus, NSF, 3-year service/labor, 5-year compressor warranty, standard, 115/600"ph, 12.6 amps, with cord & NEMA 5-20P, standard. Left door hinged left/hinged right, set. Locking keypad, padlock supplied by others, per door. Stainless steel back with real levers.	New	Floor					1651	864	2286	1201	20	60	No	Plug	No	No	No	No	No	No	No	No	No	No	No	No	Steel construction	Traulsen	ADT232DUFHS	True Manufacturing			
CDH-IP-02 ID 64	A	On Floor Food Service / Gallery (CUHCU)	1	0264.03	Waste bin with duty	Container, round, open type, 20-gallon capacity, high-impact plastic construction, grey, UL, round, for 20 gallon container, blue, 20-gallon, black.	New	Mobile						No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	Plastic Construction	Rubbermaid	Brute 2620					
CDH-IP-02 ID 64	A	On Floor Food Service / Gallery (CUHCU)	1	0264.04	Coffee Brewer and Warmers complete with hot water dispenser	Coffee Brewer, Portable, mechanical thermostat, brews 18.9 gallons per hour capacity, stainless steel funnel, 3 batch-size settings, electronic timer & grinder interface, upper hot water faucet, variable water bypass, includes (2) service, 4" back adjustable legs, 1200/600"ph, 5950 watts, 29 amps, UL, NSF, 1.5 GPR/F Coffee Server, 1.5 gallon, top handles, fast flow faucet, stainless decor, NSF, Satellite Brewer/Warmer, 4" adjustable plastic legs (for use with 1 GPR and 1.5 GPR servers), 120/600"ph, 100w, 1 amps, cord attached, UL, NSF Paper Filters, 13.3x1.14" white, (for Tea & Coffee) 1-1/2 gallon, High Water System, 25,000 gallon, reduced sediment, chlorine taste & odor, reduction @ 2.1 gpm, equipment protection, 0.2 micron, includes a head assembly, integral mounting bracket and cartridge filter, Quick Connect, NSF, Drip Tray Kit, stainless floor.	New	Counter				1200/2860	1	30	60	No	No	No	No	Direct	No	No	No	No	No	No	6	No	No	No	No	No	No	Steel Construction	Bunn	2060.0011	Felco	Curtis	
CDH-IP-02 ID 64	A	On Floor Food Service / Gallery (CUHCU)	1	0264.05	S.S. Work Table (mobile)	Stainless steel construction, type 304, #4 finish, Length to suit design x 30" wide x 34" high, stainless steel top with stainless steel or galvanized steel sub-top. Hat channel reinforcement to be stainless steel or galvanized steel on centre. Legs to be stainless steel, tubing or square welded to subtop. Stainless steel cross bracing as required. Sound deadening as required. 4 all swivel non-marking rubber cast-washable casters with brakes, S.S. drawers.	New	Mobile				Varies based on layout - typically 1524	762	864	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	Steel construction	Custom Fabricated	Custom Fabricated			
CDH-IP-02 ID 64	ME	On Floor Food Service / Gallery (CUHCU)	1	0264.06	S.S. Work Table with Sink	Stainless steel construction, type 304, #4 finish, Length to suit design x 760mm wide x 864mm high, stainless steel top with 2.0mm stainless steel or galvanized steel sub-top. Hat channel reinforcement to be stainless steel or galvanized steel on centre. Sink to be minimum 18" x 16" x 12" deep complete with hot and cold water faucet with swing spout. Legs to be stainless steel, tubing or square welded to subtop. Stainless steel cross bracing as required. Sound deadening as required. Backsplash to include radius coved corner, sprayed to wall where required. Bulet test for tables without m/e services, flanged feet secured to floor with s.s. fasteners for tables with m/e services, S.S. drawers.	New	Floor				Varies based on layout - typically *1524mm to 1628"	762	864	1201	15	60	No	No	Plug	No	No	No	No	13	13	No	No	38	No	No	No	No	No	Steel construction	Custom Fabricated	Custom Fabricated		
CDH-IP-02 ID 64	A	On Floor Food Service / Gallery (CUHCU)	1	0264.07	Microwave Oven	Commercial Microwave Oven, 0.6 cu. ft. capacity, 1200 watts, heavy volume, 4-stage cooking, (11) power levels, (100) memory settings, 60-minute max cooking time, LED display, touch control, interlock safety switch, ADR compliant touch panel, audible end of cycle signal, side hinged door with tempered glass, sealed ceramic interior shelf, lighted interior, stainless steel exterior & interior, 120/600"ph, 16.8 amps, 20 MCA, 2000 watts (total), NEMA 5-20P, eTLux, ETL Sanitation, 3-year full warranty.	New	Counter						1201	20	60	No	No	Plug	No	No	No	No	No	No	No	No	No	No	No	No	No	No	Steel construction	Amara	HDC1242	Panasonic		
CDH-IP-02 ID 64	ME	On Floor Food Service / Gallery (CUHCU)	1	0264.08	S.S. Wall Mounted Microwave Shaving	2.0mm type 304 stainless steel wall cladding to be wall mounted where impact of moisture resistance is required by design.	New	Wall Mounted			Variable	304.0	Variable	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	Steel construction	Custom Fabricated	Custom Fabricated				
CDH-IP-02 ID 64	ME	On Floor Food Service / Gallery (CUHCU)	1	0264.09	Hand Free Hand Sink	Hand Sink, pedestal mounted base, 15-1/2" wide x 9-3/4" front-to-back x 6-3/4" deep bowl, 304 stainless steel construction, splash mount gooseneck spout, pedestal valves, P-trap, tall pipe, basket drain, drain-train seamless design-positive drain, inverted "Y" edge, NSF, Antimicrobial finish on bowl only. Emergency Eye Wash Unit, faucet-mount, fits in place of aerator on spout, (2) dust covers, full valve activates fountain, polished chrome finish, Anti-Scald Valve, for emergency eye wash, 1/2" NPT, 60°-95°F (meets ANSI Z358.1 & ASSE 1017 standards). Left & right side splashes.	New	Wall	14.5	14.5	376	480	1019	No	No	No	No	No	13	13	No	No	No	No	No	38	Yes	No	No	No	No	No	No	Hands free operation with eye wash.	Eagle	HSA-10-FA-P	Advance Tabco	Custom Fabricated	
CDH-IP-02 ID 64	A	On Floor Food Service / Gallery (CUHCU)	1	0264.10	Ice / Water Dispenser	Ice / Water Dispenser, Cabinet-Style, air-cooled, self-contained condenser, production capacity up to 262 8oz cups at 77°F (21°) & AHRI certified @ 90°F (32°), 10 lb built-in storage capacity, counter mount push button operation, stainless steel bin & exterior, protected with Antimicrobial Agent, R-404A refrigerant, 4" legs, 115/600"ph, 8.5 amps, NEMA 5-15P (optional stand sold separately), NSF, UL, Warranty: 3-Year parts & labor on entire machine. Warranty: 3-Year parts on compressor, air-cooled condenser. Equipment Stand, for dispenser/dispensers, cabinet base with locking door, stainless steel, corrosion resistant exterior, with flat top, with painted flanged legs, ETL Sanitation. Complete with water filter.	New	Counter						421	613	805	1201	20	No	Plug	No	No	No	No	No	13	No	38	No	No	No	No	Steel construction	Hoshizaki	DCM-270BAH	Scottman	Folet		
CDH-IP-03 ID 103		On Floor Food Service / Gallery (MathNew Borm)			Tray delivery cart (Noted in the kitchen)		New							2893	40	60	No	Plug	No	Yes	Yes	No	No	No	No	No	No	No	No	No	No	Steel construction	Burbridge	RTS HL					
CDH-IP-03 ID 103	A	On Floor Food Service / Gallery (MathNew Borm)	1	03103.01	Combi-Oven - Ventless	Future item service to be rough-in and capped for future install	New	Floor						2893	70	60	No	Direct	No	Yes	No	No	13	No	13	No	52	No	No	No	No	No	Steel construction	Rational	SOC WE E3E 600-9-6-E	Conotherm	Budgette		
CDH-IP-03 ID 103	A	On Floor Food Service / Gallery (MathNew Borm)	1	03103.02	Reach In Dual Temp Double Door Refrigerator / Freezer	Refrigerator/Freezer Dual Temp Cabinet, reach-in, 48" wide, self-contained refrigeration, stainless steel exterior, aluminum interior, standard depth cabinet, (2) lockable full-height doors, (3) adjustable wire shelves per section, interior LED lighting, microprocessor controls, 1/5 HP & 1/3 HP, cULus, NSF, 3-year service/labor, 5-year compressor warranty, standard, 115/600"ph, 12.6 amps, with cord & NEMA 5-20P, standard. Left door hinged left/hinged right, set. Locking keypad, padlock supplied by others, per door. Stainless steel back with real levers.	New	Floor				1651	864	2286	1201	20	60	No	Plug	No	Yes	No	No	No	No	No	No	No	No	No	No	No	Steel construction	Traulsen	ADT232DUFHS	True Manufacturing			
CDH-IP-03 ID 103	A	On Floor Food Service / Gallery (MathNew Borm)	1	03103.03	Waste bin with duty	Container, round, open type, 20-gallon capacity, high-impact plastic construction, grey, UL, round, for 20 gallon container, blue, 20-gallon, black.	New	Mobile						No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	Plastic Construction	Rubbermaid	Brute 2620					
CDH-IP-03 ID 103	A	On Floor Food Service / Gallery (MathNew Borm)	1	03103.04	Coffee Brewer and Warmers complete with hot water dispenser	Coffee Brewer, Portable, mechanical thermostat, brews 18.9 gallons per hour capacity, stainless steel funnel, 3 batch-size settings, electronic timer & grinder interface, upper hot water faucet, variable water bypass, includes (2) service, 4" back adjustable legs, 1200/600"ph, 5950 watts, 29 amps, UL, NSF, 1.5 GPR/F Coffee Server, 1.5 gallon, top handles, fast flow faucet, stainless decor, NSF, Satellite Brewer/Warmer, 4" adjustable plastic legs (for use with 1 GPR and 1.5 GPR servers), 120/600"ph, 100w, 1 amps, cord attached, UL, NSF Paper Filters, 13.3x1.14" white, (for Tea & Coffee) 1-1/2 gallon, High Water System, 25,000 gallon, reduced sediment, chlorine taste & odor, reduction @ 2.1 gpm, equipment protection, 0.2 micron, includes a head assembly, integral mounting bracket and cartridge filter, Quick Connect, NSF, Drip Tray Kit, stainless floor.	New	Counter				1200/2860	1	30	60	No	No	No	No	Direct	No	Yes	No	No	No	No	6	No	No	No	No	No	No	Steel Construction	Bunn	2060.0011	Felco	Curtis	
CDH-IP-03 ID 103	A	On Floor Food Service / Gallery (MathNew Borm)	1	03103.05	S.S. Work Table (mobile)	Stainless steel construction, type 304, #4 finish, Length to suit design x 30" wide x 34" high, stainless steel top with stainless steel or galvanized steel sub-top. Hat channel reinforcement to be stainless steel or galvanized steel on centre. Legs to be stainless steel, tubing or square welded to subtop. Stainless steel cross bracing as required. Sound deadening as required. 4 all swivel non-marking rubber cast-washable casters with brakes, S.S. drawers.	New	Mobile				Varies based on layout - typically 1524	762	864	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	Steel construction	Custom Fabricated	Custom Fabricated			
CDH-IP-03 ID 103	ME	On Floor Food Service / Gallery (MathNew Borm)	1	03103.06	S.S. Work Table with Sink	Stainless steel construction, type 304, #4 finish, Length to suit design x 760mm wide x 864mm high, stainless steel top with 2.0mm stainless steel or galvanized steel sub-top. Hat channel reinforcement to be stainless steel or galvanized steel on centre. Sink to be minimum 18" x 16" x 12" deep complete with hot and cold water faucet with swing spout. Legs to be stainless steel, tubing or square welded to subtop. Stainless steel cross bracing as required. Sound deadening as required. Backsplash to include radius coved corner, sprayed to wall where required. Bulet test for tables without m/e services, flanged feet secured to floor with s.s. fasteners for tables with m/e services, S.S. drawers.	New	Floor				Varies based on layout - typically *1524mm to 1628"	762	864	1201	15	60	No	No	Plug	No	No	No	No	13	13	No	No	38	No	No	No	No	No	Steel construction	Custom Fabricated	Custom Fabricated		
CDH-IP-03 ID 103	A	On Floor Food Service / Gallery (MathNew Borm)	1	03103.07	Microwave Oven	Commercial Microwave Oven, 0.6 cu. ft. capacity, 1200 watts, heavy volume, 4-stage cooking, (11) power levels, (100) memory settings, 60-minute max cooking time, LED display, touch control, interlock safety switch, ADR compliant touch panel, audible end of cycle signal, side hinged door with tempered glass, sealed ceramic interior shelf, lighted interior, stainless steel exterior & interior, 120/600"ph, 16.8 amps, 20 MCA, 2000 watts (total), NEMA 5-20P, eTLux, ETL Sanitation, 3-year full warranty.	New	Counter						1201	20	60	No	No	Plug	No	No	No	No	No	No	No	No	No	No	No	No	No	Steel construction	Amara	HDC1242	Panasonic			
CDH-IP-03 ID 103	ME	On Floor Food Service / Gallery (MathNew Borm)	1	03103.08	S.S. Wall Mounted Microwave Shaving	2.0mm type 304 stainless steel wall cladding to be wall mounted where impact of moisture resistance is required by design.	New	Wall Mounted			Variable	304.0	Variable	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	Steel construction	Custom Fabricated	Custom Fabricated				
CDH-IP-03 ID 103	ME	On Floor Food Service / Gallery (MathNew Borm)	1	03103.09	Hand Free Hand Sink	Hand Sink, pedestal mounted base, 15-1/2" wide x 9-3/4" front-to-back x 6-3/4" deep bowl, 304 stainless steel construction, splash mount gooseneck spout, pedestal valves, P-trap, tall pipe, basket drain, drain-train seamless design-positive drain, inverted "Y" edge, NSF, Antimicrobial finish on bowl only. Emergency Eye Wash Unit, faucet-mount, fits in place of aerator on spout, (2) dust covers, full valve activates fountain, polished chrome finish, Anti-Scald Valve, for emergency eye wash, 1/2" NPT, 60°-95°F (meets ANSI Z358.1 & ASSE 1017 standards). Left & right side splashes.	New	Wall	14.5	14.5	376	480	1019	No	No	No	No	No	13	13	No	No	No	No	No	38	Yes	No	No	No	No	No	Hands free operation with						





Appendix 2K-1 Food Service Equipment List  
 Updated January 24, 2022

ID	Category	Department Room Reference	Total Qty	Item Ref No	Item Description	Long Description	Item Status	Mounting	Max Weight (kg)	Ship Weight (kg)	Width (mm)	Depth (mm)	Height (mm)	Volts	Amps	Hz	Watts	Plug Type	BTU/hr	Dedicated Circuit	Tech Connection (Yes)	Emergency Power	Water-Cold	Water-Hot	Water-Treated	Steam	Drain	Vent	Gas	Vacuum-Dental	Vacuum-Med	Compressed Air	Item Notes	Sample Manufacturer 1	Sample Model 1	Sample Manufacturer 2	Sample Manufacturer 3		
OS-GR-05 ID 23	ME	Cafe/Bistro	1	05.23.20	Cashier station		New	Counter						120V	21	60	No	Plug	No	Yes	No	No	No	No	No	No	No	No	No	No	No								
OS-GR-05 ID 23	A	Cafe/Bistro	1	05.23.21	Point of sale system		New	Counter						120V	15	60	No	Plug	No	Yes	Yes	No	No	No	No	No	No	No	No	No	No								
OS-GR-05 ID 23	A	Cafe/Bistro	3	05.23.22	Menu boards		New	Counter						120V	15	60	No	Plug	No	Yes	Yes	No	No	No	No	No	No	No	No	No	No								
OS-GR-05 ID 23	ME	Cafe/Bistro	1	05.23.23	Stainless steel hand sink	Hand Sink, pedestal mounted base, 13-1/2" wide x 9-3/4" front-to-back x 6-3/4" deep bowl, 304 stainless steel construction, splash mount gooseneck spout, pedal valves, P-trap, tall pipe, basket drain, deep-drain seamless design-positive drain, inverted "V" edge NSF, Antimicrobial finish on bowl only, Emergency Eye Wash Unit, faucet-mount, fits in place of aerator on spout, (2) dust covers, pull valve activates fountain, polished chrome finish, Anti-Scald Valve, for emergency eye wash, 1/2" NPT, 65-95°F (meets ANSI Z358.1 & ASSE 1017 standards). Left & right side splashplates.	New	Wall	14.5	14.5	376	480	1019	No	No	No	No	No	No	No	No	No	No	13	13	No	No	38	Yes	No	No	No	No		Eagle	HSA-10-FA-P	Advance Tabco	Custom Fabricated	
OS-GR-05 ID 23	A	Cafe/Bistro	1	05.23.24	Utility cart	Utility Cart, 33.5"x18.5"x37.5" H, 200 lb. capacity, (3) shelves, smooth surface, handles, open sides, plastic construction, brushed aluminum uprights, (4) 4" wheel casters, assembly required, black, HACCP, Made in USA.	New	Mobile	14	14	473	854	959	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No		Plastic Construction	Rubbermaid	FG3424888LA	Metro	Camro		
CDH OS-TL-05 ID 38	ME	Indigenous Kitchen - Incoming Receiving Area	1	05.38.01	Stainless steel hand sink	Hand Sink, pedestal mounted base, 13-1/2" wide x 9-3/4" front-to-back x 6-3/4" deep bowl, 304 stainless steel construction, splash mount gooseneck spout, pedal valves, P-trap, tall pipe, basket drain, deep-drain seamless design-positive drain, inverted "V" edge NSF, Antimicrobial finish on bowl only, Emergency Eye Wash Unit, faucet-mount, fits in place of aerator on spout, (2) dust covers, pull valve activates fountain, polished chrome finish, Anti-Scald Valve, for emergency eye wash, 1/2" NPT, 65-95°F (meets ANSI Z358.1 & ASSE 1017 standards). Left & right side splashplates.	New	Wall	14.5	14.5	376	480	1019	No	No	No	No	No	No	No	No	No	No	13	13	No	No	38	Yes	No	No	No	No		Eagle	HSA-10-FA-P	Advance Tabco	Custom Fabricated	
CDH OS-TL-05 ID 38	A	Indigenous Kitchen - Incoming Receiving Area	1	05.38.02	Platform cart	Platform Truck, 24"W x 50"D x 35"H, 2000 lbs. capacity, removable high end handle, steel construction, powder coat finish, (2) 6" casters, NSF listed, Corner Bumpers (set of 2)	New	Mobile	46	46	610	1270	889	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No		Steel construction	Channel Manufacturing	PT2448	Hatch	Custom Fabricated			
CDH OS-TL-05 ID 38	A	Indigenous Kitchen - Incoming Receiving Area	1	05.38.03	Utility cart	Utility Cart, 33.5"x18.5"x37.5" H, 200 lb. capacity, (3) shelves, smooth surface, handles, open sides, plastic construction, brushed aluminum uprights, (4) 4" wheel casters, assembly required, black	New	Mobile	14	14	473	854	959	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No		Plastic Construction	Rubbermaid	FG3424888LA	Metro	Camro		
CDH OS-TL-05 ID 39	ME	Indigenous Kitchen - Refrigerated Storage Room	1	05.38.04	Pre-fabricated insulated wall and ceiling panels and- refrigeration system	ULC listed pre-fabricated insulated wall and ceiling panels, 4" (100mm) thick with polyurethane insulation. Panels to have a tongue and groove configuration and fastened together with a mechanical cam-lock fastener. Finish to be stainless steel. Room complete with 914mm wide x 2130 mm high hinged door complete with heated viewing window. All rooms complete with LED light fixtures to provide 50 foot candle lighting levels. Stainless steel tread plates on all exposed exterior.	New	Floor	Custom	Custom	Custom	Custom	Custom	120V	15	60	No	Direct	No	Yes	No	Yes	No	No	No	No	No	No	No	No	No		Custom Fabricated Panel Construction	Norbac	Custom	Canadian Curtis	Masterbuilt		
CDH OS-TL-05 ID 39	ME	Indigenous Kitchen - Refrigerated Storage Room	1	05.38.05	Refrigeration evaporator coil	Stand and balanced to match the compressor(s) and must be capable of maintaining internal room temperature (max. +32 for coolers, min. -18C for freezers) while considering humidity levels of surrounding areas, product type and load, heat infiltration and temperature of incoming product. Concession free assembly. Time initiated air defrost cycles for coolers. Electric or hot gas defrost for freezers.	New	Floor	Custom	Custom	Custom	Custom	Custom	120V	15	60	No	Direct	No	Yes	No	Yes	No	No	No	No	Yes	No	No	No	No		Custom Fabricator	Norbac	Custom	Canadian Curtis	Masterbuilt		
CDH OS-TL-05 ID 39	ME	Indigenous Kitchen - Refrigerated Storage Room	1	05.38.06	Refrigeration condensing unit	Remote Water Cooled Condensing unit sized to suit walk-in room size. Unit to include mounting on top of the room. Rack design/ refrigeration system would be considered if it can be accommodated within the design.	New	Floor	Custom	Custom	Custom	Custom	Custom	208V	20	60	No	Direct	No	Yes	No	Yes	No	No	No	No	No	No	No	No		Custom Fabricator	Norbac	Custom	Canadian Curtis	Masterbuilt			
CDH OS-TL-05 ID 39	ME	Indigenous Kitchen - Refrigerated Storage Room	1	05.38.07	Temperature Alarm	Hi-low temperature alarm, recessed in wall panels, with dry contacts for remote monitoring, rechargeable battery having operating range of -50C to +50C. Capillary temperature bulbs to be positioned behind evaporator coils (no visible wires). Interconnected to building automation system and remote monitoring and logging system.	New	Floor	Custom	Custom	Custom	Custom	Custom	120V	15	60	No	Direct	No	Yes	Yes	Yes	No	No	No	No	No	No	No	No	No		Custom Fabricator	Norbac	Custom	Canadian Curtis	Masterbuilt		
CDH OS-TL-05 ID 39	A	Indigenous Kitchen - Refrigerated Storage Room	4	05.38.08	Shelving unit	Constructed of steel with removable polypropylene overlays or polyester, thermoplastic/polypropylene construction. Construction to be corrosion resistant and coated with anti-microbial substance. Minimum dimensions to be 610mm wide. All units to include cart washable casters, two locking. Minimum four tiers of shelves. Shelves to be adjustable. Overall dimension of unit to vary depending on the layout of the room. Typically 1220mm or 1524mm wide.	New	Mobile	5	5	610	Varies based on layout - typically 1220mm to 1524mm	1752	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No		Plastic Construction	Metro	Max Q	Camro			
CDH OS-TL-05 ID 39	A	Indigenous Kitchen - Refrigerated Storage Room	1	05.38.09	Dunnage rack	Weight Capacity: 1500lbs, Plastic Storage Rack for Food, Molded Polyethylene Or Polymer Seamless Construction w/ Antimicrobial Protection. Slotted Top For Air Circulation. Side Run Front To Back.	New	Floor				910	550	305	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No		Plastic Construction	Metro	HP2236PD					
CDH OS-TL-05 ID 40	ME	Indigenous Kitchen - Frozen Store Room	1	05.38.10	Pre-fabricated insulated wall and ceiling panels and- refrigeration system	ULC listed pre-fabricated insulated wall and ceiling panels, 4" (100mm) thick with polyurethane insulation. Panels to have a tongue and groove configuration and fastened together with a mechanical cam-lock fastener. Finish to be stainless steel. Room complete with 914mm wide x 2130 mm high hinged door complete with heated viewing window. All rooms complete with LED light fixtures to provide 50 foot candle lighting levels. Stainless steel tread plates on all exposed exterior.	New	Floor	Custom	Custom	Custom	Custom	Custom	120V	15	60	No	Direct	No	Yes	No	Yes	No	No	No	No	No	No	No	No	No		Custom Fabricated Panel Construction	Norbac	Custom	Canadian Curtis	Masterbuilt		
CDH OS-TL-05 ID 40	ME	Indigenous Kitchen - Frozen Store Room	1	05.38.11	Refrigeration evaporator coil	Stand and balanced to match the compressor(s) and must be capable of maintaining internal room temperature (max. +32 for coolers, min. -18C for freezers) while considering humidity levels of surrounding areas, product type and load, heat infiltration and temperature of incoming product. Concession free assembly. Time initiated air defrost cycles for coolers. Electric or hot gas defrost for freezers.	New	Floor	Custom	Custom	Custom	Custom	Custom	120V	15	60	No	Direct	No	Yes	No	Yes	No	No	No	Yes	No	No	No	No	No		Custom Fabricator	Norbac	Custom	Canadian Curtis	Masterbuilt		
CDH OS-TL-05 ID 40	ME	Indigenous Kitchen - Frozen Store Room	1	05.38.12	Refrigeration condensing unit	Remote Water Cooled Condensing unit sized to suit walk-in room size. Unit to include mounting on top of the room. Rack design/ refrigeration system would be considered if it can be accommodated within the design.	New	Floor	Custom	Custom	Custom	Custom	Custom	208V	20	60	No	Direct	No	Yes	No	Yes	No	No	No	No	No	No	No	No	No		Custom Fabricator	Norbac	Custom	Canadian Curtis	Masterbuilt		
CDH OS-TL-05 ID 40	ME	Indigenous Kitchen - Frozen Store Room	1	05.38.13	Temperature Alarm	Hi-low temperature alarm, recessed in wall panels, with dry contacts for remote monitoring, rechargeable battery having operating range of -50C to +50C. Capillary temperature bulbs to be positioned behind evaporator coils (no visible wires). Interconnected to building automation system and remote monitoring and logging system.	New	Floor	Custom	Custom	Custom	Custom	Custom	120V	15	60	No	Direct	No	Yes	Yes	Yes	No	No	No	No	No	No	No	No	No		Custom Fabricator	Norbac	Custom	Canadian Curtis	Masterbuilt		
CDH OS-TL-05 ID 40	A	Indigenous Kitchen - Frozen Store Room	4	05.38.14	Shelving unit	Constructed of steel with removable polypropylene overlays or polyester, thermoplastic/polypropylene construction. Construction to be corrosion resistant and coated with anti-microbial substance. Minimum dimensions to be 610mm wide. All units to include cart washable casters, two locking. Minimum four tiers of shelves. Shelves to be adjustable. Overall dimension of unit to vary depending on the layout of the room. Typically 1220mm or 1500mm wide.	New	Mobile	5	5	610	Varies based on layout - typically 1220mm to 1524mm	1752	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No		Plastic Construction	Metro	Max Q	Camro			
CDH OS-TL-05 ID 40	A	Indigenous Kitchen - Frozen Store Room	1	05.38.15	Dunnage rack	Weight Capacity: 1500lbs, Plastic Storage Rack for Food, Molded Polyethylene Or Polymer Seamless Construction w/ Antimicrobial Protection. Slotted Top For Air Circulation. Side Run Front To Back.	New	Floor				910	550	305	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No		Plastic Construction	Metro	HP2236PD					
CDH OS-TL-05 ID 41	A	Indigenous Kitchen - Preparation Area	1	05.38.16	Shelving unit	Constructed of steel with removable polypropylene overlays or polyester, thermoplastic/polypropylene construction. Construction to be corrosion resistant and coated with anti-microbial substance. Minimum dimensions to be 610mm wide. All units to include cart washable casters, two locking. Minimum four tiers of shelves. Shelves to be adjustable. Overall dimension of unit to vary depending on the layout of the room. Typically 1220mm or 1500mm wide.	New	Mobile	5	5	610	Varies based on layout - typically 1220mm to 1524mm	1752	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No		Plastic Construction	Metro	Max Q	Camro				
CDH OS-TL-05 ID 41	ME	Indigenous Kitchen - Preparation Area	1	05.38.17	Stainless steel table with sink	Stainless steel construction, type 304, #4 finish, length to suit design x 760mm wide x 864mm high, stainless steel top with 2.0mm stainless steel or galvanized steel sub-top. Hot channel reinforcement to be stainless steel or galvanized steel on centre. Sinks to be minimum 18" x 15" x 12" deep complete with hot and cold water faucet with swing spout. Legs to be stainless steel, tubing or square welded to subtop. Stainless steel cross bracing as required. Sound deadening as required. Backsplash to include splash pad, cast washable casters with where required. Bulket feet for tables without m/e services, flanged feet secured to floor with s.s. fasteners for tables with m/e services. S.S. drawers.	New	Floor	Custom	Custom	Varies based on layout - typically 762mm-1067mm	762	864	120V	15	60	No	Plug	No	No	No	No	No	No	13	13	No	No	38	No	No	No	No		Steel construction	Custom Fabricated	Custom Fabricated		
CDH OS-TL-05 ID 41	ME	Indigenous Kitchen - Preparation Area	1	05.38.18	Stainless steel table	Stainless steel construction, type 304, #4 finish, length to suit design x 760mm wide x 864mm high, stainless steel top with stainless steel or galvanized steel sub-top. Hot channel reinforcement to be stainless steel or galvanized steel on centre. Legs to be stainless steel, tubing or square welded to subtop. Stainless steel cross bracing as required. Sound deadening as required. 4 all level non-marring rubber cast washable casters with brakes. S.S. drawers.	New	Floor	Custom	Custom	Varies based on layout - typically 762mm-1067mm	762	864	120V	15	60	No	Plug	No	No	No	No	No	No	No	No	No	No	No	No	No	No		Steel construction	Custom Fabricated	Custom Fabricated			
CDH OS-TL-05 ID 41	ME	Indigenous Kitchen - Preparation Area	1	05.38.19	Stainless steel overhead	Stainless steel construction, type 304, #4 finish, length to suit design x 300mm wide x 1500mm high, stainless steel top with stainless steel or galvanized steel sub-top. Hot channel reinforcement to be stainless steel or galvanized steel on centre.	New	Wall	Custom	Custom	To align with workable underneath	304.8	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No		Steel construction	Custom Fabricated	Custom Fabricated					
CDH OS-TL-05 ID 41	A	Indigenous Kitchen - Preparation Area	1	05.38.20	Utility cart	Utility Cart, 33.5"x18.5"x37.5" H, 200 lb. capacity, (3) shelves, smooth surface, handles, open sides, plastic construction, brushed aluminum uprights, (4) 4" wheel casters, assembly required, black	New	Mobile	14	14	473	854	959	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No		Plastic Construction	Rubbermaid	FG3424888LA	Metro	Camro		
CDH OS-TL-05 ID 41	A	Indigenous Kitchen - Preparation Area	2	05.38.21	Waste bin with duty	Container, round, open top, 20-gallon capacity, high-impact plastic construction, grey, UL listed, round, for 20 gallon container. Body, duty containers, black.	New	Mobile						No	No	No	No	No	No	No	No	No	No	No	No	No	No	No	No		Plastic Construction	Rubbermaid	Brute 2020						
CDH OS-TL-05 ID 41	A	Indigenous Kitchen	1	05.38.22	Counter slicer w/ Mobile Stand	Heavy Duty Metal Slicer, Automatic, 17" Commercial, removable knife and arched front with (5) interlocks, (3) stroke lengths & (4) stroke speeds, removable meat grip assembly, removable ring guard cover, product fence, single action top mounted sharpener with Borazon™ stones, manual 90 lever, 1/2 hp motor, 120V/60Hz/1-øp NSF (ETL) List. Standard warranty: 1 Year limited warranty. Food chute for HS series slicers. Product deflector for HS series slicers. Product deflector for HS series slicers.	New	On stainless steel table			494	760	646	120V	15	60	No	Plug	No	Yes	No	No	No	No	No	No	No	No	No	No	No		Steel construction	Hobart	H59-1	Globe			
CDH OS-TL-05 ID 44	A	Indigenous Kitchen	1		Reach-In Dual Temp. Refrigerator / Freezer	Refrigerator/Freezer Dual Temp. Cabinet, reach-in, 18" wide, well-ventilated refrigeration, stainless steel exterior, aluminum interior, standard depth, double doors, 21 cubic feet storage space, 20" wide wheels, two doors per section, interior LED lighting, temperature controls, 1.6 HP & 1.0 HP, 120V, NSF - 3 year commercial, 5-year compressor warranty, stainless-1166Wx1912Hx1245D mm with casters and 4MM-Ø-20IP stainless-1616mm-1616mm height adjusting legs, 2" solid top, padlock supplied by customer, pad door. Stainless steel back with casters.	New	Floor			2551	864	2266	220V	20	60	No	Plug	No	Yes	No	Yes	No	No	No	No	No	No	No	No	No		Steel construction	Traulsen	AD1232UL-414G	True Manufacturing			
CDH OS-TL-05 ID 41	ME	Indigenous Kitchen	1	05.38.24	Stainless steel hand sink	Hand Sink, pedestal mounted base, 13-1/2" wide x 9-3/4" front-to-back x 6-3/4" deep bowl, 304 stainless steel construction, splash mount gooseneck spout, pedal valves, P-trap, tall pipe, basket drain, deep-drain seamless design-positive drain, inverted "V" edge NSF, Antimicrobial finish on bowl only, Emergency Eye Wash Unit, faucet-mount, fits in place of aerator on spout, (2) dust covers, pull valve activates fountain, polished chrome finish, Anti-Scald Valve, for emergency eye wash, 1/2" NPT, 65-95°F (meets ANSI Z358.1 & ASSE 1017 standards). Left & right side splashplates.	New	Wall	14.5	14.5	376	480	1019	No	No	No	No	No	No	No	No	No	13	13	No	No	38	Yes	No	No	No	No		Eagle	HSA-10-FA-P	Advance Tabco	Custom Fabricated		
CDH OS-TL-05 ID 42	ME	Indigenous Kitchen	1	05.38.25	Exhaust hood with fire protection system	The hood shall be designed with Side-Jet technology to reduce the exhaust airflow rate required, and to improve the capture and containment efficiency of the hood, while reducing energy consumption. The Side-Jet technology shall be introduced through a special discharge panel and shall not exceed 10% of the calculated exhaust airflow. The Side-Jet technology discharge velocity will be a minimum of 1500 feet per minute. Slot or grille type discharge shall not be used. The Side-Jet technology shall be internally mounted in a speed control and will not require a fire damper or electronic shut down in the fire mode. The integral front discharge grille or air plenum shall be manufactured of the same material as the hood. The face of the plenum shall be perforated stainless steel to deliver low velocity air to the space and reduce room turbulence while refreshing the occupied zone. The SFP fire suppression system is an industry leader in rugged components and superior fire suppression. The versatile SFP system incorporates a stored pressure cylinder and delivers a wet chemical agent to a fire, quickly suppressing and containing fires in a wide variety of applications.	New	Ceiling					See Long Description	See Long Description	See Long Description	2 @ 120V	20	60	No	Direct	No	Yes	No	Yes	No	No	No	No	No	No	No	No		CFM I.B.C. Type I Hood	Habon	KVE	Spring-Ar	Gaylor	
CDH OS-TL-05 ID 42	A	Indigenous Kitchen	1	05.38.26	Combination steam convection oven, electric - 10 GN capacity w/ stand	Combi Oven/Steamer, electric, (10) 18" x 26" full size sheet or (20) 12" x 20" full size hotel pan capacity. Control with 7 modes, Combi-Steamer with 3 modes, core temp probe with 5 point measurement, hand shower with automatic recharging system, mobile oven included, (10) 16" stainless, 4" manual interface, 208V/60/3-øp, 103 amps, 36.0 kW, 2 years parts and labor, 5 years steam generator warranty, Manufacture Technical Start-Up, electric units, by an authorized service company. Water Filtration Double Cartridge System, for Combi-Duo if space for more than 2 units includes: (1) double head with pressure gauge, (2) filter & (1) filter canister. Each additional unit add (1) additional head & additional cartridge. Maximum (4) cartridges). The carbon block technology reduces the effects of sediment, chloramines and chlorine while providing the required flow rates. Heat Shield, for left side panel. Unit Connection Kit, includes: water connection hose 1/2" (2") w/ 3/4" union & DN 50mm (2") unit drain set (6 x HT-bow 87", 2 x HT-bow 45", 4 x HT-ops 500mm, 1 x sleeve). Externally attached core temperature probe. Control panel protection. Mobile stand with casters (4) with locks.	New	Floor			105																												

